

Special Products

SB 90° Curved Elbow, Metric, Metal, Swivel

- For applications with high technical requirements, mainly in machine building
- Suitable for occasional rotation
- High-grade formulated polyamide 6, thread and integrated swivel adapter made from nickel-plated brass
- Very high impact resistance
- High thread and system connection strength
- Suitable for occasional rotation
- Round guidance within the connector
- Easy introduction of wires and cables
- Vibration-proof connection to PMAFLEX® conduits
- Very good chemical properties
- Free from halogens and cadmium
- Fits fine (T) and coarse (G) conduit profiles



CAT. NO. IP68, BLACK	THREAD METRIC	FITS TO CONDUIT SIZE			EXTERNAL DIMENSIONS
		NW	METRIC	THREAD LENGTH	
NSBV-M207-10	M20x1.5	17	20	10.0mm	62.5 x 74.5mm
NSBV-M253-11	M25x1.5	23	25	11.0mm	73.0 x 87.5mm
NSBV-M329-13	M32x1.5	29	32	13.0mm	86.5 x 98.0mm
NSBV-M406-13	M40x1.5	36	40	13.0mm	98.5 x 127.5mm
NSBV-M409-13	M40x1.5	29	32	13.0mm	86.5 x 98.0mm
NSBV-M508-14	M50x1.5	48	50	14.0mm	113.0 x 139.0mm
NSBV-M638-14	M63x1.5	48	50	14.0mm	110.0 x 139.0mm



Temperature range: -40° C to 105° C;
Short term to 160° C

Content of delivery:

Fitting with oval clips (OVN2),
conduit and thread seals (NVN3, SVN4 or OR)

SB 90° Curved Elbow, PG, Metal, Swivel

- For applications with high technical requirements, mainly in machine building
- Suitable for occasional rotation
- High-grade formulated polyamide 6, thread and integrated swivel adapter made from nickel-plated brass
- Very high impact resistance
- High thread and system connection strength
- Suitable for occasional rotation
- Round guidance within the connector
- Easy introduction of wires and cables
- Vibration-proof connection to PMAFLEX® conduits
- Very good chemical properties
- Free from halogens and cadmium
- Fits fine (T) and coarse (G) conduit profiles



CAT. NO. IP68, BLACK	THREAD PG	FITS TO CONDUIT SIZE			EXTERNAL DIMENSIONS
		NW	METRIC	THREAD LENGTH	
NSBV-P167-6.5	16	17	20	6.5mm	58.0 x 75.5mm
NSBV-P213-7	21	23	25	7.0mm	69.0 x 87.5mm
NSBV-P299-8	29	29	32	8.0mm	80.0 x 98.0mm
NSBV-P366-9	36	36	40	9.0mm	91.5 x 127.5mm
NSBV-P488-10	48	48	50	10.0mm	106.0 x 139.0mm



Temperature range: -40° C to 105° C;
Short term to 160° C

Content of delivery:

Fitting with oval clips (OVN2), conduit and thread seals (NVN3, SVN4 or OR)

SWA Swivel Adapters, Metric

- Allow PMA® connectors to swivel freely in applications where such movements is occasionally necessary
- Nickel-plated brass
- Connect to PMA® connectors with metal threads
- Include thread edge protection
- Include corresponding seals up to IP67/IP68

CAT. NO. IP67	THREAD METRIC	OUTSIDE DIAMETER	DIMENSIONS LENGTH
SWA-M16-10	M16x1.5	23.0mm	37.5mm
SWA-M20-10	M20x1.5	27.0mm	38.5mm
SWA-M25-11	M25x1.5	32.0mm	41.0mm
SWA-M32-13	M32x1.5	45.0mm	46.5mm
SWA-M40-13	M40x1.5	55.0mm	47.5mm
SWA-M50-14	M50x1.5	59.0mm	49.5mm
SWA-M63-14	M63x1.5	75.0mm	52.0mm



Temperature range: -40° C to 105° C

Content of delivery:

Adapter, thread seal (SVN4 or OR)