

Special Products

SWA Swivel Adapters, PG

- Allow PMA® connectors to swivel freely in applications where such movements is occasionally necessary
- Nickel-plated brass
- Connect to PMA connectors with metal threads
- With thread edge protection
- With corresponding seals up to IP67/IP68

CAT. NO. IP67	THREAD PG	OUTSIDE DIAMETER	DIMENSIONS LENGTH
SWA-P09	9	23.0mm	44.5mm
SWA-P11	11	27.0mm	45.5mm
SWA-P16	16	32.0mm	48.0mm
SWA-P21	21	40.0mm	51.0mm
SWA-P29	29	50.0mm	52.0mm
SWA-P36	36	59.0mm	55.0mm
SWA-P48	48	70.0mm	55.0mm



Temperature range: -40° C to 105° C

Content of delivery:

Adapter, thread seal (SVN4 or OR)

SCA Spin Couplers, Metric

- Allow the easy positioning of elbow connectors with metal threads
- Nickel-plated brass
- Connect to PMA® connectors with metal threads
- High fastening torque
- Include thread edge protection
- Up to IP68 (IEC 60529/EN 60529)

CAT. NO. IP68	THREAD METRIC	OUTSIDE DIAMETER	DIMENSIONS LENGTH
SCA-M16-10	M16x1.5	22.0mm	32.0mm
SCA-M20-10	M20x1.5	26.0mm	33.0mm
SCA-M25-11	M25x1.5	32.0mm	35.0mm
SCA-M32-13	M32x1.5	39.0mm	39.5mm
SCA-M40-13	M40x1.5	50.0mm	41.0mm
SCA-M50-14	M50x1.5	59.0mm	43.5mm
SCA-M63-14	M63x1.5	75.0mm	45.5mm



Temperature range: -40° C to 105° C

Content of delivery:

Adapter, thread seal (SVN4)

SCA Spin Couplers, PG

- Allow the easy positioning of elbow connectors with metal threads
- Nickel-plated brass
- Connect to PMA® connectors with metal threads
- High fastening torque
- Include thread edge protection
- Up to IP68 (IEC 60529/EN 60529)

CAT. NO. IP68	THREAD PG	OUTSIDE DIAMETER	DIMENSIONS LENGTH
SCA-P09	9	22.0mm	35.0mm
SCA-P11	11	26.0mm	36.0mm
SCA-P16	16	29.0mm	38.0mm
SCA-P21	21	39.0mm	41.0mm
SCA-P29	29	44.0mm	42.5mm
SCA-P36	36	59.0mm	49.0mm
SCA-P48	48	69.0mm	50.5mm



Temperature range: -40° C to 105° C

Content of delivery:

Adapter, thread seal (SVN4)