

PVC-Coated Conduit Bodies and Fittings

Make 90° bends while allowing straight pulls! **Ocal-Blue Double-Coat Pulling Elbows**



LBD and LBH bodies are installed at 90° bends in rigid conduit to act as pull outlets for conductors that are stiff due to large size or type of insulation and to make 90° bends in conduit system while allowing straight wire pulls in either direction.

- Choose LBD series for ordinary locations and LBH series for hazardous locations
- Coated with a nominal .002" (2 mil) blue urethane on both interior and exterior
- Nominal .040" (40 mil) PVC coating bonded to exterior
- · Pressure-sealing sleeves seal connections

Cat. No. LBD1100 = space for color identified	Color .—
G = Gray	
W = White	
B = Blue	
Custom colors also available.	


ORDINARY LBD SERIES CAT. NO.	HAZARDOUS LBH SERIES** CAT. NO.	PIPE SIZE IN. METRIC SIZE DESIGNATOR*
LBD1100	LBH10	1/2
		16
LBD2200	LBH20	3/4
		21
LBD3300	LBH30	1
		27
LBD4400	LBH40	11/4
I BBEEGG	LBUE	35
LBD5500	LBH50	1½
I DDCC00	LDUCO	41 2
LBD6600	LBH60	2 53
LBD7700-	LBH70-	2½
LDD1100	LDII/U	63
LBD8800-	LBH80-	3
EDD0000	LDIIOU	78
LBD9900-	LBH90-	3½
	_	91
LBD10900-	LBH100-	4
	_	103
LBD012	_	5
		129
LBD014	_	6
		15

- * Metric size designator (ANSI C80.1-1994).
- ** Ratings prior to PVC coating



BLB4-G Mogul





Ocal-Blue® Double-Coat Mogul Fittings

Install mogul fittings in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of installation, to provide the longer openings needed when pulling large conductors, to prevent sharp bends and kinks in large conductors or to provide more splicing space.

- Nominal .002" (2 mil) blue urethane on both interior and exterior
- Nominal .040" (40 mil) PVC coating bonded to exterior
- · Pressure-sealing sleeves protect connections



BG48-G Replacement Cover

MOGUL FITTING WITH COVER AND GASKET			- REPLACEMENT	PIPE SIZE				
BC CAT. NO.	BLB CAT. NO.	BUB Cat. No.	BT Cat. No.	COVER BG CAT. NO.	IN. Metric Size Designator*			
BC3	BLB3	BUB3	ВТ3	BG48	1 27			
BC4	BLB4	BUB4	BT4	BG48	1¼ 35			
BC5	BLB5	BUB5	BT5	BG68	1 ½ 41			
BC6	BLB6	BUB6	BT6	BG68	2 53			
BC7	BLB7	BUB7	BT7	BG88	2½ 63			
BC8	BLB8	BUB8	BT8	BG88	3 78			
BC9	BLB9	BUB9	BT9	BG98	3½ 91			
BC10	BLB10	BUB10	BT10	BG98	4 103			
^ ivietric size des	* Metric size designator (ANSI C80.1-1994).							

www.tnb.com

United States

Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354 Technical Services
Tel: 888.862.3289

