


## Hubs and Bulkhead Fittings

UL Listed rain tight and CSA Certified watertight and dust tight.

### Steel/Malleable Iron and Aluminum Bullet® Hub Connectors\*†

- Available in steel/malleable iron (steel through 1") with nylon-insulated throat — with or without Series 106 bonding locknut
- Also available in aluminum without insulated throat
- When used with neoprene O-ring, provides watertight threaded hub on enclosures
- UL Listed 105° C
- Look for the unique T&B blue color ensuring the highest quality fitting



CAT. NO.			HUB SIZE (IN.)	DIMENSIONS (IN.)			MAX. WALL THICKNESS (IN.)
STEEL/M.I.	ALUM.**	STEEL/M.I. W/LOCKNUT		A	B	C	
370	370AL	401	1/2"	1 3/8	1 1/4	3/4	5/16
371	371AL	402	3/4	1 3/8	1 1/4	3/4	5/16
372	372AL	403	1"	2 3/32	1 3/8	7/8	5/16
373	373AL	404-TB	1 1/8"	2 9/16	1 3/8	1	5/16
374	374AL	405	1 1/2"	3 3/32	1 5/8	1	5/16
375	375AL	406-TB	2"	3 5/8	1 5/8	1	5/16
376	—	407	2 1/2"	4 1/8	1 5/8	1 1/8	3/8
377	—	408	3"	5	2 1/2	1 1/2	1/2
378	—	409	3 1/2"	5 9/16	2 1/2	1 1/2	1/2
379	—	410-TB	4"	6 3/16	2 1/2	1 1/2	1/2
381	—	—	5"	8	3 3/8	—	1/2
382	—	—	6"	9 3/16	3 3/8	—	1/2

\* Suitable for hazardous locations use in Class I, Div. 2; Class II, Div. 2; Class III, Div. 1 and 2 where general purpose equipment is specifically permitted per NEC Section 500-2(a).

Available with DURA-PLATE® finish.

UL File No. E-23018

\*\* Aluminum not available with insulated throat.

For Stl.: CSA File No. 2284

† UL Listed rain tight and CSA Certified watertight and dust tight

For AL.: CSA File No. 0637

### Spacing Chart for Bullet® Hubs

	CENTER-TO-CENTER SPACING CONDUIT SIZES												MIN. SPACE FROM CENTER OF BULLET® HUB TO WALL OF BOX	KO DIAMETERS (MIN.)
	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	3 1/2	4	5	6		
1/2	1 1/16	1 1/8	1 1/4	2 1/8	2 3/8	2 7/8	2 7/8	3 3/16	3 1/2	3 3/8	4 7/8	5 1/16	3/4	7/8
3/4	—	1 1/4	1 7/8	2 1/4	2 1/2	2 3/4	3	3 1/2	3 3/4	4 1/8	4 13/16	5 1/2	7/8	1 1/8
1	—	—	2	2 3/8	2 5/8	2 7/8	3 1/8	3 3/8	3 3/8	4 1/4	4 15/16	5 11/16	1 1/8	1 3/8
1 1/4	—	—	—	2 11/16	2 15/16	3 1/4	3 1/2	4	4 1/4	4 1/2	5 1/8	5 3/4	1 3/8	1 3/4
1 1/2	—	—	—	—	3 1/8	3 1/2	3 3/4	4 1/8	4 3/8	4 3/4	5 1/8	6 1/8	1 5/8	2
2	—	—	—	—	—	3 3/4	4	4 1/2	4 3/4	5	5 3/4	6 1/2	1 7/8	2 1/2
2 1/2	—	—	—	—	—	—	4 1/4	4 3/4	5	5 3/8	6	6 3/4	2 1/8	3
3	—	—	—	—	—	—	—	5 1/8	5 3/8	5 3/4	6 3/8	7 1/8	2 3/8	3 3/8
3 1/2	—	—	—	—	—	—	—	—	5 3/8	6	6 3/4	7 1/2	2 3/8	4 1/8
4	—	—	—	—	—	—	—	—	—	6 1/4	7 1/8	7 3/8	3 1/4	4 3/8
5	—	—	—	—	—	—	—	—	—	—	8	8 3/4	4	5 1/2
6	—	—	—	—	—	—	—	—	—	—	—	8 3/4	9 1/2	6 1/2

## PVC-Coated Conduit and Accessories

Support conduit on walls and structures.

### Pipe Straps



Two-Hole PVC-Coated Pipe Strap

One-Hole PVC-Coated Pipe Strap

- Available in malleable iron/stamped steel with nominal .015" (15 mil) PVC coating in your choice of blue, white or gray or in 303 stainless steel
- Choose one- or two-hole versions
- Sized to allow for the extra thickness of the PVC coating



Two-Hole Stainless Steel Pipe Strap

One-Hole Stainless Steel Pipe Strap

### 303 Stainless Steel Pipe Straps for PVC-Coated Conduit

CAT NO.		PIPE SIZE IN. METRIC SIZE DESIGNATOR*	CONDUIT STRAP I.D. IN. MM	PVC-COATED CONDUIT O.D. IN. MM
ONE-HOLE 303 S.S. STRAP	TWO-HOLE 303 S.S. STRAP			
TS102-SS	TS902-SS	1/2	.92	.92
		16	23.37	23.37
TS103-SS	TS903-SS	3/4	1.16	1.13
		21	29.46	28.70
TS104-SS	TS904-SS	1	1.51	1.40
		27	38.35	35.56
TS105-SS	TS905-SS	1 1/4	1.74	1.74
		35	44.20	44.20
TS106-SS	TS906-SS	1 1/2	2.20	1.98
		41	55.88	50.29
HS107-SS	HS907-SS	2	2.88	2.46
		53	73.15	62.48
HS108-SS	HS908-SS	2 1/2	3.50	2.96
		63	88.90	75.18
HS109-SS	HS909-SS	3	4.00	3.98
		78	101.60	101.09
HS110-SS	HS910-SS	3 1/2	4.50	4.08
		91	114.30	103.63

\* Metric size designator (ANSI C80.1-1994).

Use as spacers with one-hole pipe straps.

### Ocal® PVC-Coated Clamp-Back Spacers



- Provides space for air flow between conduit and mounting surface
- Nominal .015" (15 mil) PVC coating for corrosion protection

CAT. NO.	PIPE SIZE IN. METRIC SIZE DESIGNATOR*
CB1/2- <sub>  </sub>	1/2
	16
CB3/4- <sub>  </sub>	3/4
	21
CB1- <sub>  </sub>	1
	27
CB1-1/4- <sub>  </sub>	1 1/4
	35
CB1-1/2- <sub>  </sub>	1 1/2
	41
CB2- <sub>  </sub>	2
	53
CB2-1/2- <sub>  </sub>	2 1/2
	63
CB3- <sub>  </sub>	3
	78
CB3-1/2- <sub>  </sub>	3 1/2
	91
CB4- <sub>  </sub>	4
	103

Cat. No.	Color
<b>CB1 -</b>	<b>—</b>
<sub>  </sub> = space for color identifier	
<b>G</b> = Gray	
<b>W</b> = White	
<b>B</b> = Blue	
Custom colors also available.	