

Rigid Conduit/IMC Fittings

Insulated Bushings — Iron/Zinc Plated




CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
BI-901	1/2	1 1/2	1/2	1,000
BI-902	3/4	1 1/4	1/2	1,000
BI-903	1	1 5/8	5/8	500
BI-904	1 1/4	1 7/8	3/4	200
BI-905	1 1/2	2 1/4	3/4	100

UL File No. E-23018.



CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
BI-906	2	2 5/8	3/4	50
BI-907	2 1/2	3 1/2	3/4	30
BI-908	3	3 7/8	3/4	25
BI-909	3 1/2	4 1/4	3/4	25
BI910	4	4 5/8	2 3/4	25



Insulated Grounding Bushings

- Die-cast zinc
- Tin-plated aluminum lay-in lug
- Three lug mounting locations




CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE CAPACITY	DIMENSIONS (IN.)		STD. CTN.
			A	B	
BG801L	1/2	—	1 1/2	1/2	500
BG802L	3/4	#14-#4 CU	1 1/4	1/2	500
BG803L	1	or	1 5/8	5/8	250
BG804L	1 1/4	#12-#4 AL	1 7/8	3/4	150
BG805L	1 1/2	—	2 1/4	3/4	150

UL File No. E-3060.



CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE CAPACITY	DIMENSIONS (IN.)		STD. CTN.
			A	B	
BG806L	2	—	2 5/8	3/4	100
BG807L	2 1/2	#14-1/0 CU	3 1/8	3/4	60
BG808L	3	or #12-1/0 AL	3 5/8	3/4	30
BG809L	3 1/2	#6-250 kcmil	4 1/8	3/4	30
BG810L	4	CU or AL	4 5/8	2 3/4	30



Grounding Bushings Malleable Iron/Zinc Plated — Insulated with Aluminum Lug

- For copper or aluminum bare ground wire
- 105° C thermoplastic liners
- Heavy reinforced ribs



CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE SIZE		STD. CTN.
		MIN.	MAX.	
BG801A	1/2	14 AWG	6 AWG	500
BG-802A	3/4	14 AWG	6 AWG	500
BG-803A	1	14 AWG	6 AWG	250
BG-804A	1 1/4	14 AWG	2 AWG	200
BG-805A	1 1/2	14 AWG	2 AWG	100
BG-806A	2	14 AWG	2 AWG	100

UL File No. E-3060.



CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE SIZE		STD. CTN.
		MIN.	MAX.	
BG-807A	2 1/2	14 AWG	2/0 AWG	50
BG-808A	3	14 AWG	2/0 AWG	50
BG-809A	3 1/2	14 AWG	2/0 AWG	10
BG-810A	4	14 AWG	2/0 AWG	10
BG-810B	4	6 AWG	250 kcmil	10

Reducing Bushings

- RB-121 thru RB-165 — Steel
- RB-175 thru RB-187 — Malleable iron (concrete tight), zinc plated



CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
RB-121	3/4-1/2	3/8	1/4	100
RB-131	1-1/2	5/8	1 1/8	50
RB-132	1-3/4	3/4	1 1/4	50
RB-141	1 1/4-1/2	1 1/8	1 1/8	50
RB-142	1 1/4-3/4	1 1/8	1 1/8	50
RB-143	1 1/4-1	1 1/8	1 1/8	50
RB-151	1 1/2-1/2	2 3/8	1 11/16	50
RB-152	1 1/2-3/4	2 3/8	1 11/16	50
RB-153	1 1/2-1	2 3/8	1 11/16	50
RB-154	1 1/2-1 1/4	2 3/8	1 11/16	50

UL File No. E-23018.



CAT. NO.	CONDUIT SIZE (IN.)	DIMENSIONS (IN.)		STD. CTN.
		A	B	
RB-161	2-1/2	2 7/8	2 3/8	25
RB-162	2-3/4	2 7/8	2 3/8	25
RB-163	2-1	2 7/8	2 3/8	25
RB-164	2-1 1/4	2 7/8	2 3/8	25
RB-165	2-1 1/2	2 7/8	2 3/8	25
RB-175	2 1/2-1 1/2	7/8	2 13/16	25
RB-176	2 1/2-2	7/8	2 13/16	25
RB-186	3-2	2 9/8	2 1/8	25
RB-187	3-2 1/2	2 9/8	2 1/8	25

