


## Copper Lugs

### Tin-Plated Two-Hole Straight and Stacking NEMA Lugs for general applications

- Provides high-conductivity, minimizes voltage drop
- Resists corrosion
- Provides 3/4 in. and 7/8 in. bolt hole centers for added versatility
- UL Listed and CSA Certified



Straight Lug Cat. No.	Stacking Lug Cat. No.	Wire Size	Bolt Size	Installing Dies	Dimensions						
					B	C	L	P	S	W	H
L 6-214		#6	1/4	7, TE, 27	1-1/8	5/16	2-13/16	1-5/16	5/8	7/16	
L 6-2516			5/16		1-1/8	5/16	2-11/16	1-5/16	5/8	7/16	
L 6 N			1/2		1-1/8	5/8	5	3-1/8	1-3/4	3/4	
L 4-214		#4	1/4	5/16, 8, TP, 29, IC, 1	1-1/8	5/16	2-3/4	1-5/16	5/8	1/2	
L 4-2516			5/16		1-1/8	5/16	2-3/4	1-5/16	5/8	1/2	
L 4 N			1/2		1-1/8	5/8	5	3-1/8	1-3/4	3/4	
L 2-214		#2	1/4	3/8, 10, TL-TN, 33, 162	1-1/4	3/8	3-1/8	1-1/2	5/8	5/8	
L 2-2516			5/16		1-1/4	3/8	3-5/16	1-5/8	3/4 - 7/8	5/8	
L 2 N			1/2		1-1/4	5/8	4-3/4	3	1-5/16	3/4	
L 1-214		#1	1/4	3/8, 11, TB, 37	1-3/8	3/8	3-3/8	1-5/8	5/8	11/16	
L 1-2516			5/16		1-1/2	5/16	3-3/8	1-5/8	3/4 - 7/8	11/16	
L 1 N			1/2		1-1/2	5/16	4-7/8	3	1-3/4	3/4	
L 1/0-238		1/0	3/8	1/2, 12, TQ, 42, 163	1-3/8		3-7/16	1-5/8	7/8	3/4	
L 1/0-2516			5/16		1-3/8		3-7/16	1-5/8	3/4 - 7/8	3/4	
L 1/0 N			1/2		1-7/16		4-7/8			3/4	
L 2/0-238		2/0	3/8	9/16, 13, TS, 45, 164	1-1/2		5-1/16			7/8	
L 2/0 N	SL 2/0 N		1/2		1-1/2		5-1/16			7/8	1-1/2
L 3/0-238			3/8		1-1/2		5-1/8			15/16	-
L 3/0 N	SL 3/0 N	1/2	1-1/2		5-1/8			15/16	1-5/8		
L 4/0-238		4/0	3/8	5/8-1, 15, TW-TY, 54, 243	1-5/8		5-3/16			11/16	-
L 4/0 N	SL 4/0 N		1/2		1-5/8		5-3/16	3		11/16	1-9/16
L 250-238			3/8		1-11/16		5-3/16			1-1/8	-
L 250 N	SL 250 N	1/2	1-11/16		5-7/16			1-1/8	1-11/16		
L 300-238		300	3/8	781, 17, TV, 66, 11/16	2	5/8	5-3/4			1-1/4	-
L 300 N	SL 300 N		1/2		2		5-3/4			1-1/4	1-3/4
L 350-238			3/8		2		5-3/4			1-15/16	-
L 350 N	SL 350 N	1/2	1-7/8	840, 18, TX, 71	2		5-3/4		1-15/16	-	
L 400-238		400	3/8	15/16, 19, TX, 76, 840	2-1/8		6	3-1/16		1-7/16	
L 400 N	SL 400 N		1/2		2-1/8		6	3-1/8		1-7/16	2-1/8
L 500 N	SL 500 N		500		1/2	1, 20, TH, 87, 251	2-1/4		6-1/16	3-1/8	1-9/16
L 600 N	SL 600 N	600	1/2	1 (1/8-1), 22, 96	2-5/8		6-3/4	3-1/8	1-11/16	2-3/16	
L 750 N	SL 750 N	750	1/2	1-5/16, 106, 24	2-13/16		7	3-1/8	1-3/4	2-5/8	
L 1000 NT	SL 1000 NT	1000	1/2	27, 1-1/2, 125	2-15/16		7-1/4	3-1/4	1-3/4	3	
L 1250 N*		1250	1/2	150, 29, 1-5/8	3		7-3/8	3-3/8	2-3/16		
L 1500 N*		1500	1/2	1-3/4, 31, 150	3-3/16		7-1/2	3	2-11/16	-	
L 2000 N*		2000	1/2	2.00, 34, 175	3-3/16		8-1/16	3-3/16	3-1/16		

The "N" suffix on the catalogue number indicates NEMA bolt spacing of 1-3/4 in. For other available sizes, please consult your Thomas & Betts representative.  
 \* L 1250 N, L 1500 N and L 2000 N are not UL Listed or CSA Certified.