

URD Multi-Port Bus Connectors and Covers



FS 95-6


Aluminum Flood-Seal™ 95 Series Service Entrance Connectors

Suitable for direct burial or installation in an enclosure

- Ideal for residential application
- Use with aluminum or copper lugs from #12 to 350 kcmil
- Safe and reliable
- Ensures that connectors are 100 % watertight and molded correctly
- Approved by the Federal government for utility use

95 Series Service Entrance Connectors

Cat. No.	Outlets	L
FS 95-2	2	2-3/4
FS 95-3	3	4-1/4
FS 95-4	4	5-3/4
FS 95-5	5	7-1/4
FS 95-6	6	8-3/4
FS 95-7	7	10-1/4
FS 95-8	8	11-3/4
FS 95-9	9	13-1/4
FS 95-10	10	14-3/4



Flood-Seal™ 95 Series Terminal Kits

Kits have insulating outlet sleeve or heat-shrink sleeve and lug.

- Universal use
- Prevent oxidation and keep out moisture



CFB 350 CS

95 Series Terminal Kits

Premolded Kit Cat. No.	Heat-Shrink Kit Cat. No.	Concentric	Compressed	Compact	Solid	Die Reference
CFG 8 CS	CFG 8 HS	#8	-	-	#6	5/8, BG, 687, 243, TU, 52, 8A
CFG 6 CS	CFG 6 HS	#6	#6	#6	-	
CFG 4 CS	CFG 4 HS	#4	#4	#4	-	
CFG 2 CS	CFG 2 HS	#2	#2	#2 & #1	#1	
CFG 1 CS	CFG 1 HS	#1	#1	1/0	1/0	840, 324, 349, 658, TX, 76, 11A
CFG 1/0 CS	CFG 1/0 HS	1/0	1/0	2/0	2/0	
CFK 1/0 CS	CFK 1/0 HS	2/0	2/0	3/0	3/0	
CFK 2/0 CS	CFK 2/0 HS	3/0	3/0	4/0	4/0	
CFK 3/0 CS	CFK 3/0 HS	4/0	4/0	250	-	(1-1/8)-1, 299-655, 96, 13A, 321, 326
CFK 4/0 CS	CFK 4/0 HS	250	250	300	-	
CFB 250 CS	CFB 250 HS	300	300	350	-	
CFB 300 CS	CFB 300 HS	336.4-350	300	350	-	
CFB 350 CS	CFB 350 HS					

For a hex-headed bolt, add "-H" suffix to the catalogue number. Force-Fit Kit includes (1) dual-rated aluminum center-formed lug, (1) 3/8 in. Allen head mounting bolt, (1) Belleville washer and (1) insulating Flood-Seal™ rocket. Heat-Shrink Kit includes (1) dual-rated aluminum center-formed lug, (1) 3/8 in. Allen head mounting bolt, (1) Belleville washer and (1) heat-shrink tubing.