

## URD Multi-Port Bus Connectors and Covers

### Aluminum Flood-Seal™ 125 Series Connectors

Choose one-way configuration or two-way configuration

- Use with aluminum or copper lugs from #12 to 500 kcmil
- Ensures cooler operation and more reliable joints
- Accept standard one- or two-hole NEMA aluminum or copper lugs
- Ensures that connectors are 100% watertight and molded correctly
- Safe and reliable
- All Flood-Seal™ connectors comply with ANSI C119.4
- Approved by the Federal government for utility use

#### One-Way Configuration

One-Bolt Design Cat. No.	Two-Bolt Design Cat. No.	Outlets	L
FS 2-125	FSN 2-125	2	3-1/2
FS 3-125	FSN 3-125	3	5-3/8
FS 4-125	FSN 4-125	4	7-1/4
FS 5-125	FSN 5-125	5	9-1/8
FS 6-125	FSN 6-125	6	11
FS 7-125	FSN 7-125	7	12-7/8
FS 8-125	FSN 8-125	8	14-3/4
FS 9-125	FSN 9-125	9	16-5/8
FS 10-125	FSN 10-125	10	18-1/2



#### Two-Way Configuration

One-Bolt Design Cat. No.	Two-Bolt Design Cat. No.	Outlets	L
FS 11-48	FS 11	2	1-1/2
FS 22-48	FS 22	4	3-3/8
FS 33-48	FS 33	6	5-1/4
FS 44-48	FS 44	8	7-1/8
FS 55-48	FS 55	10	8-7/8
FS 66-48	FS 66	12	10-3/4
FS 77-48	FS 77	14	12-5/8
FS 88-48	FS 88	16	14-1/2
FS 99-48	FS 99	18	16-3/8

To order insulating EPDM sleeves for Two-Hole connectors, see page C31. Order lugs separately.

