



Fig.1



Fig.2



Fig.3



Fig.4

Aluminum Lugs

Blackburn® Slotted-Tang Compression Terminal Lugs

Compress these lugs with standard tools and dies

- Use with a wide range of aluminum and copper conductors
- Prevents oxidation and keeps out moisture
- Boss fits the indent on the bus, preventing the lug from rotating
- The bus doesn't have to be removed
- RUS Listed

Cat. No.	Colour Code	Conductor Size			Fig. No.	Installation Dies	
		Concentric	Compressed Compact	Sol.		Mech. Tool	Hydr. Tool
LAC6	Blue	#6 str.	#6	#5	1	BY37, 840	B49EA, U-K840
LAC4	Orange	#4 str.	#4	#3.			
LAC3	Purple	#3 str.	-	#2			
LAC2	Red	#2 str.	#2	#1			
LAC1	White	#1 str.	#1	1/0			
LAC10	Yellow	1/0 str.	1/0	2/0			
LAC20	Grey	2/0 str.	2/0	3/0	2	BY37, 840U	B49EA, K840
LAC30	Black	3/0 str.	3/0	4/0			
LAC40	Pink	4/0 str.	4/0	-			
LAC42	Orange	#4 str.	#4	#3			
LAC32	Purple	#3 str.	-	#2			
LAC22	Red	#2 str.	#2	#1			
LAC12	White	#1 str.	#1	1/0			
LAC102	Yellow	1/0 str.	1/0	2/0			
LAC202	Grey	2/0 str.	2/0	3/0			
LAC302	Black	3/0 str.	3/0	4/0			
LAC402	Pink	4/0 str.	4/0		3	-	B80EA, 1.1, 655
LAC25	Green	350, 266.6	250				
LAC35	Brown	300, 350	350				
LAC50	Aqua	400, 500	500				
LAC125	Green	250, 266.8	250				
LAC135	Brown	300, 350	350				
LAC150	Aqua	400, 500	500		4		