Marine Products Ship-to-Shore Selection Chart - Boatside

30A **125V AC** 2 Pole 3 Wire







Pages 5-9

HBL303NM HBL303SSBL

HBL303SS

HBL26CM13

HBL60CM33 HBL60CM33W

50A 125V AC 2 Pole 3 Wire











Pages 10-11, 14

50A 125/250V AC 3 Pole 4 Wire



HBL504NM



HBL504RI







HBL77CM15W

Pages 12-14

100A 125/250V AC



HBL504SS

HBL77CM15 HBL77CM15W HBL63CM64

3 Pole 4 Wire





M4100C12R

Pages 15-17

100A 3ØY 4 Pole 5 Wire







Pages 15, 18-19 120/208V AC 277/480V AC

200A 600V AC/250V DC 4 Pole 5 Wire

M5100B7R

M5100C9R M5100C7R



M5200BS1R



Pages 20-21

Portable Telephone Cable TV



Wiring Device-Kellems









Pages 26-27

HBLPHTVNM

HUBBELL

HBLPHTVSS

PH6624 PH7440

Marine Products

Telephone and Cable TV Devices Ship-to-Shore Devices



HBLPHTVNM



HBLPHTVSS



HBLTVSS



PH6625



PH6624



PH7440

Telephone and Cable TV Ship-to-Shore Devices

Description	Catalog Numbers
Stylized non-metallic inlet provides telephone and cable TV connections in one unit. UV resistant white Centrex® cover makes unit weatherproof when completely closed. Mounting holes are 2.38 in. (60.3) on centers and match existing mounting patterns. Mounting screws and gasket provided. IP56 SUITABILITY.	HBLPHTVNM
Stylized Type 316 stainless steel inlet provides telephone and cable TV connections in one unit. Easy to use push-button latch makes unit watertight when fully engaged. Mounting holes are 2.38 in. (60.3) on centers and match existing mounting patterns. Mounting screws and gasket provided. IP56 SUITABILITY.	HBLPHTVRI ∆
Traditional stainless steel inlet provides connections for telephone and cable TV in one unit. Connections can be used individually or together. Gasketed cover is self-closing so interior is shielded from the elements when not in use. Watertight when cover is screwed in place. Mounting holes are 2.38 in. (60.3) on centers. Mounting screws and gasket included. IP56 SUITABILITY.	HBLPHTVSS
Same as HBLPHTVSS above except no phone.	HBLTVSS
Replacement int. for PH6594TV and HBLPHTVSS series inlets.	CR16914
Factory pre-wired 50 ft. (15.2m) telephone cable set. Uses 3 conductor, #16 AWG type SJTO, yellow vinyl cord for marine and recreational vehicle applications. IP55 SUITABILITY .	PH6599
Same as PH6599 except white.	PH6599W
Same as PH6599 except 25 ft. (7.6m) in length.	PH6598
Same as PH6598 except white.	PH6598W
Black locking type plug for telephone cable sets or adapters.	PH6625
Black locking type connector body used on telephone cable sets or adapters.	PH6624
Yellow Seal-Tite® cover for weatherproofing PH6624 connector body on cable sets when connecting to an inlet and for weatherproofing PH6625 plug. IP55 suitability.	PH7440
Yellow Seal-Tite cover for weatherproofing PH6624 connector body when used on extension cords or adapters. IP55 SUITABILITY.	PH7499

Note: Δ To be discontinued when present stocks are exhausted.



Centrex® is a registered trademark of LANXESS Corporation.