

60A, 125/250V, 3 Pole, 4 Wire Grounding, Receptacles and Plugs

IP20
SUITABILITY




**60A 125/250V
NEMA 14-60R
UL CSA
3(2) HP**



**60A 125/250V
NEMA 14-60P
UL CSA
3(2) HP**

Description	Cord Diameter	Catalog Number	
Receptacle, black RTP.	-	HBL9460A	-
Plug, nylon.	.625"-1.310" (15.9-33.3)	-	HBL9461C
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	-	HBL9462C



HBL9460A

60A, 3Ø 250V AC, 3 Pole, 4 Wire Grounding, Receptacles and Plugs

IP20
SUITABILITY



**60A 3Ø 250V AC
NEMA 15-60R
UL CSA
10 HP**



**60A 3Ø 250V AC
NEMA 15-60P
UL CSA
10 HP**

Description	Cord Diameter	Catalog Number	
Receptacle, black RTP.	-	HBL8460A	-
Plug, nylon.	.625"-1.310" (15.9-33.3)	-	HBL8461C
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	-	HBL8462C



HBL8461C



HBL8462C

60A, 3ØY 120/208V AC, 4 Pole, 4 Wire Non-Grounding, Receptacles and Plugs

IP20
SUITABILITY




**60A 3ØY
120/208V AC
NEMA 18-60R
UL Listed
7.5 HP**



**60A 3ØY
120/208V AC
NEMA 18-60P
UL Listed
7.5 HP**

Description	Cord Diameter	Catalog Number	
Receptacle, black RTP.	-	HBL7301A	-
Plug, nylon.	.625"-1.310" (15.9-33.3)	-	HBL7303C
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	-	HBL7302C



HBL7301A

Note: RTP is an abbreviation for reinforced thermoplastic polyester.
See page A-50 for accessories.

Dimensions in Inches (mm)