
Straight Blade Devices

15 and 20 Ampere, 125 Volts







HBL8300SGA



HBL8200ILW





00 HBL8210GY

Dimensions in Inches (mm)

IP20 15A 125V NEMA 5-15F HBL[®] Extra Heavy Duty UL CSA 0.5 HP Hospital Grade Receptacles Duplex Color Catalog Number Flush, thermoplastic polyester face, Black HBL8200BK back and side wired. Blue Brown HBL8200 HBL8200GY Grav lvory HBL8200I HBL8200LA Light Almond HBL8200RED Red HBL8200W White Flush, LED illuminated face, HBL8200ILGY Gray back and side wired. lvory HBL8200ILI Red HBL8200ILR White HBL8200ILW HBL8200SGA Tamper-Resistant receptacle Brown

with wire leads. Complies with

requirements of NEC® article

517-18(c).

Isolated ground⁴. Orange IG8200 IG8300 Red IG8200R IG8300R **MRI Receptacle, Duplex** MRI receptacle, flush, thermoplastic HBL8200IMRI HBL8300IMRI lvory polyester face, back and side wired. Light Almond HBL8200LAMRI HBL8300LAMRI 100% non-ferrous. Red HBL8200RMRI HBL8300RMRI White HBL8200WMRI HBL8300WMRI Slender/Compact, Duplex Flush, thermoplastic polyester face, Brown HBL8200H HBL8300H HBL8200HG back, and side wired. Grav HBL8300HG HBL8300HGN Fed. Spec. verified. Green HBL8200HI HBL8300HI lvory Light Almond HBL8200HLA HBL8300HLA HBL8200HRED HBL8300HRED Red White HBL8200HW HBL8300HW Style Line[®] Decorator* Flush, nylon face, HBL2172 HBL2182 Brown back and side wired. HBL2172GY HBL2182GY Gray HBL2172I HBL2182I lvory Office White **HBL2182OW** Red HBL2172R HBL2182R HBL2172WA White HBL2182WA Isolated ground^A. IG2182I lvory Orange _ IG2182 IG2182WA White _ Single HBL8310AL Flush, nylon face, Almond back and side wired. Brown HBL8210 HBL8310 Fed. Spec. verified. Gray HBL8210GY HBL8310GY HBL8210I HBL8310I lvory Red HBL8210R HBL8310R White HBL8210W HBL8310W Panel mount on 1.94 in. Brown HBL8284 (49.2) centers. HBL8284I HBL8384I lvory IG8210 IG8310 Isolated ground^A. Orange Note: ^ASee section N for additional information on isolated ground devices.

Gray

lvory Light Almond

Red

White

*Not Fed. Spec. Listed. See pages A-47 and A-48 for accessories.

See page Tech-10 for Tamper-Resistant description.

See section M for additional information on Hospital Grade products.

See section O for wallplates.

NEC® is a registered trademark of the National Fire Protection Association (NFPA).

(5P)

00

[] []~w

20A 125V NEMA 5-20R UL CSA 1 HP

HBL8300BL

HBL8300GY

HBL8300LA

HBL8300W

HBL8300ILI

HBL8300ILR

HBL8300ILW

HBL8300SGA

HBL8300SGIA

HBL8300SGLA

HBL8300SGRA

HBL8300SGWA

HBL8300SGGYA

HBL8300RED

HBL8300ILGY

HBL8300

HBL8300I

ŪĞ

W

HBL8200SGGYA


HBL8200SGIA

HBL8200SGRA


HBL8200SGWA

A-8


Hospital Products




USB8300C5W




USB8200AC5W



HBL8210GY







HBL4API

Hospital Grade USB Charger Type-C, Type A&C and Type A		15A 125V NEMA 5-15R UL CSA 0.5 HP	20A 125V NEMA 5-20R UL CSA 1 HP
Description	Color	Catalog Number	
Hospital Grade USB Charger Outlet: two Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	Black Brown Gray Ivory Light Almond Red White	USB8200C5BK USB8200C5 USB8200C5GY USB8200C5I USB8200C5LA USB8200C5R USB8200C5W	USB8300C5BK USB8300C5 USB8300C5GY USB8300C5I USB8300C5LA USB8300C5R USB8300C5W
Hospital Grade USB Charger Outlet: one Type A and one Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	Black Brown Gray Ivory Light Almond Red White	USB8200AC5BK USB8200AC5 USB8200AC5GY USB8200AC5I USB8200AC5I USB8200AC5LA USB8200AC5R USB8200AC5W	USB8300AC5BK USB8300AC5 USB8300AC5GY USB8300AC5I USB8300AC5LA USB8300AC5R USB8300AC5W
Hospital Grade USB Charger Outlet: two Type A port configurations, high power 5 Amp, 5 Volt USB output,	Black Brown Gray	USB8200A5BK USB8200A5 USB8200A5GY	USB8300A5BK USB8300A5 USB8300A5GY

lvory

Red

White

Light Almond

ΠĞ

[]

USB8200A5I

USB8200A5LA

USB8200A5R

USB8200A5W

[]w

ŪĞ

0 þw

USB8300A5I

USB8300A5LA

USB8300A5R

USB8300A5W

Note: See page A-7 for additional information on USB charger devices.

Tamper-Resistant duplex receptacle,

USB ports rated 10,000 cycles.

HBL [®] Extra Heavy Duty Hospital Grade ● Single Re	SUITA	20 BILITY	Fed.Spec.
Description	Color	Catalog Number	
Flush, nylon face,	Almond	-	HBL8310AL
back and side wired,	Brown	HBL8210	HBL8310
Fed. Spec. verified.	Gray	HBL8210GY	HBL8310GY
	lvory	HBL8210I	HBL8310I
	Red	HBL8210R	HBL8310R
	White	HBL8210W	HBL8310W
Panel mount on 1.94 in.	Brown	HBL8284	-
(49.2) centers.	lvory	HBL8284I	HBL8384I
Isolated ground [∆] .	Orange	IG8210	IG8310

Note: Δ See section N for additional information on isolated ground devices.

4-PLEX [®] Hospital Grade ● F	Receptacles		
Description	Color	Catalog Number	
4 outlet high impact resistant	Brown	HBL415H	HBL420H
Polycarbonate construction.	Gray	-	HBL420HGY
Mount to 4 in. square box.	lvory	HBL415HI	HBL420HI
	Red	HBL415HR	HBL420HR
	White	HBL415HW	HBL420HW

4-PLEX® Accessories

Description	Color	Catalog Number	
4-PLEX adapter plates for 1- and 2-gang, device boxes.	Brown Gray Ivory Red White	HBL4AP HBL4APGY HBL4API HBL4APR HBL4APW	HBL4AP HBL4APGY HBL4API HBL4APR HBL4APW

Note: See page A-28 for additional information on 4-PLEX devices.

Dimensions in Inches (mm)