


20 Amp, 347, 480, 600 and 125/250 Volts AC
2 Pole, 3 Wire, Grounding and 3 Pole, 3 Wire, Non-Grounding

IP20
SUITABILITY




HBL2341




HBL2345



HBL2343



HBL2340



HBL2346

Dimensions in Inches (mm)

Plugs

| Description | Cord Dia. | Catalog Number | | | |
|------------------------------------|-------------------------|----------------|----------------|----------------|----------------|
| Black and white nylon. | .360"-.930" (9-24) | HBL3721 | HBL2341 | HBL2351 | - |
| Black and white nylon (Not shown). | .300"-1.050" (7.6-26.7) | - | - | - | HBL2361 |

Note: See page B-52 for accessories.

Flanged Inlets

| Description | Catalog Number | | | |
|---------------------------|----------------|----------------|----------------|----------------|
| Nylon casing, back wired. | HBL3725 | HBL2345 | HBL2355 | HBL2365 |

Note: See page B-52 for accessories.

IP20
SUITABILITY



Connector Bodies

| Description | Cord Dia. | Catalog Number | | | |
|------------------------------------|-------------------------|----------------|----------------|----------------|----------------|
| Black and white nylon. | .360"-.930" (9-24) | HBL3723 | HBL2343 | HBL2353 | - |
| Black and white nylon (Not shown). | .300"-1.050" (7.6-26.7) | - | - | - | HBL2363 |

Note: See page B-52 for accessories.

Single Flush Receptacles

| Description | Catalog Number | | | |
|--|----------------|------------------|----------------|----------------|
| Black nylon face, back and side wired. | HBL3720 | HBL2340 | HBL2350 | HBL2360 |
| Watertight Safety-Shroud®, gray Valox® housing and flange, back and side wired, (Not shown). | - | HBL2340SW | - | - |
| Isolated ground, orange nylon face, back and side wired. | - | IG2340 | - | - |

Note: See page B-52 for accessories.

Flanged Receptacles

| Description | Catalog Number | | | |
|---------------------------|----------------|----------------|----------------|----------------|
| Nylon casing, back wired. | HBL3726 | HBL2346 | HBL2356 | HBL2366 |

Note: See page B-52 for accessories.

See page B-69 for technical information.
 See page B-39 for switched enclosure.
 See page B-42 for Add-A-Shroud® kit. For use with connector bodies.
 Only receptacles and plugs up to 480V AC are HP rated.
 HP ratings are AC only.

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.