

**20 Amp, 3ØY 120/208, 277/480 and 347/600 Volts AC  
4 Pole, 5 Wire, Grounding**




**HBL2511SW**




**HBL2511S**



**HBL2511**



**HBL2515SW**



**HBL2515**

Dimensions in Inches (mm)



**HBL3PT2511**

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.



**20A 3ØY 120/208V AC  
NEMA L21-20P  
2 HP**



**20A 3ØY 277/480V AC  
NEMA L22-20P  
5 HP**



**20A 3ØY 347/600V AC  
NEMA L23-20P**

## Plugs

### Watertight Safety-Shroud®

Description	Cord Dia.	Catalog Number	IP66 SUITABILITY	UL Type 4x, 12
Black Valox® housing, white Valox® clamps.	.350"-1.150" (9-29)	<b>HBL2511SW</b>	-	-

### Safety-Shroud®

Description	Cord Dia.	Catalog Number	IP20 SUITABILITY	UL Type 4x, 12
Black and white nylon body, white Valox® shroud. Can be used with the Insulgrip Connector Bodies.	.350"-1.150" (9-29)	<b>HBL2511S</b>	-	-

Note: See page B-40 for accessories.

### Insulgrip®

Description	Cord Dia.	Catalog Number	IP20 SUITABILITY	UL Type 4x, 12
Black and white nylon.	.350"-1.150" (9-29)	<b>HBL2511</b>	<b>HBL2521</b>	<b>HBL2531</b>
All black nylon.	.350"-1.150" (9-29)	<b>HBL2511BK</b>	-	-
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)	<b>HBL25CM11</b>	-	-
Black and white for flat cable.	.350"-1.150" (9-29)	<b>HBL2511FC</b>	-	-

Note: See page B-52 for accessories.

## Flanged Inlets

### Watertight Safety-Shroud®

Description	Catalog Number	IP66 SUITABILITY	UL Type 4x, 12
Gray Valox® housing and flange.	<b>HBL2515SW</b>	-	-

Note: See page B-52 for accessories.

### Insulgrip®

Description	Catalog Number	IP20 SUITABILITY	UL Type 4x, 12
Nylon casing, back wired.	<b>HBL2515</b>	<b>HBL2525</b>	<b>HBL2535</b>

Note: See page B-52 for accessories.

See pages B-69 and B-70 for technical information on Twist-Lock and Watertight Safety-Shroud devices.

## Twist-Lock® 3-Phase Circuit Tester



Description	Rating	Catalog Number	IP66 SUITABILITY	UL Type 4x, 12
3-Phase Circuit Tester	3Ø 120/208V AC Min. Voltage: 90V AC	<b>HBL3PT2511</b>	-	-

Note: Testers in other NEMA configurations can be developed upon request. See page B-53 for additional circuit testers.



**HBLMITL** - For use with Watertight Safety-Shroud receptacles, see page B-41.