## 30 Amp, 125/250 and 3Ø 250 Volts AC 3 Pole, 3 Wire, Non-Grounding and 3 Pole, 4 Wire, Grounding

			<u> </u>	0111
Watertight Safety-Shroud®		IP66 s	SUITABILITY UL	Type 4x, 12
Description	Cord Dia.	Catalog Number		
Black Valox <sup>®</sup> housing, white Valox <sup>®</sup> clamps.	.350"-1.150" (9-29)	-	HBL2713SW	HBL2723SW
Reverse service, black Valox <sup>®</sup> housing, white Valox <sup>®</sup> clamps (use with HBL2715SWR), (Not shown).	.350"-1.150" (9-29)	-	HBL2713SR	-
Insulgrip®			IP20 SUITABILITY	
Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	-	HBL2713	HBL2723
Black and white nylon, (Not shown).	.300"950" (7.6-24.1)	HBL2663	-	-
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)	-	HBL27CM13	HBL27CM23

x 🖙

**NEMA L10-30R** 

JI.

**NEMA L14-30R** 

HBL2713BK

D

30A 3Ø 250V A NEMA L15-30F

\_



HBL2713SW

F(VL)S

**SP** 



HBL2713

Note: See page B-52 for accessories.

**Connector Bodies** 

## **Receptacles**

All black nylon.

Watertight Safety-Shroud <sup>®</sup>	IP66	SUITABILITY	UL 1	Гуре 4х, 12
Description	Catalog Number			
Gray Valox <sup>®</sup> housing and flange, back wired.	-	HBL2710	SW	HBL2720SW
Note: See page B-54 for accessories.				
Safety-Shroud <sup>®</sup> Twist-Lock <sup>®</sup>	IP20 SUITABILITY			
Description	Catalog Number			

-

.350"-1.150"


(9-29)

Description	Oatalog Number		
Gray Valox <sup>®</sup> angle housing, one gang, back wired.	-	HBL2710AR	HBL2720AR
Gray Valox <sup>®</sup> surface mounting, one gang, back wired.	-	HBL2710SR	HBL2720SR
Gray Valox <sup>®</sup> semi-flush, two gang, back wired.	-	HBL2710SR2	HBL2720SR2
Single Flush Receptacles		IP20 SUITABILITY	Y
Description	Catalog Number		
Black nylon face, back and side wired.	-	HBL2710	HBL2720
Black nylon face, back and side wired, (Not shown).	HBL2660	-	-
Isolated ground, orange nylon face, back and side wired.	-	IG2710	IG2720
Ring terminal connection.	-	HBL2710RT	HBL2720RT
Nata Ora and D 50 fee and and			


Note: See page B-52 for accessories.

## Insulgrip<sup>®</sup> Flanged Receptacles

Description	Catalog Number			
Nylon casing, back wired.	-	HBL2716	HBL2726	
NUL O DEGI				







Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.







Dimensions in Inches (mm)

HUBBELL<sup>®</sup> Wiring Device-Kellems

- 5.12" -(130.0)

HBL2710SR2

.77"\_ (19.6)