

Twist-Lock® Devices



**30 Amp, 3Ø 480 and 3Ø 600 Volts AC
3 Pole, 4 Wire, Grounding**



**30A 3Ø 480V AC
NEMA L16-30R
10 HP**

**30A 3Ø 600V AC
NEMA L17-30R**

Connector Bodies

Watertight Safety-Shroud®

Description	Cord Dia.	IP66 SUITABILITY	UL Type 4x, 12	Catalog Number
Black Valox® housing, white Valox® clamps.	.350"-1.150" (9-29)			HBL2733SW HBL2743SW



HBL2733SW

Insulgrip®

Description	Cord Dia.	IP20 SUITABILITY	Catalog Number
Black and white nylon.	.350"-1.150" (9-29)		HBL2733 HBL2743
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)		HBL27CM33 HBL27CM43



HBL2733

Note: See page B-52 for accessories.

Receptacles

Watertight Safety-Shroud®

Description	Catalog Number
Gray Valox® housing and flange, back wired.	HBL2730SW HBL2740SW

Note: See page B-54 for accessories.

Safety-Shroud® Twist-Lock®

Description	Catalog Number
Gray Valox® angle housing, one gang, back wired.	HBL2730AR HBL2740AR
Gray Valox® surface mounting, one gang, back wired.	HBL2730SR HBL2740SR
Gray Valox® semi-flush, two gang, back wired.	HBL2730SR2 HBL2740SR2



HBL2730SW

Single Flush Receptacles

Description	Catalog Number
Black nylon face, back and side wired.	HBL2730 HBL2740

Note: See page B-52 for accessories.


Insulgrip® Flanged Receptacles

Description	Catalog Number
Nylon casing, back wired.	HBL2736 HBL2746


Note: See page B-52 for accessories.




HBL2730AR




HBL2736



HBL2730



HBL2730SR2



HBL2730SR

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)