

# Twist-Lock® Devices


**Non-NEMA 20 Amp, 250, 125/250 Volts and 3ØY 120/208 Volts AC  
2 Pole, 3 Wire, Grounding and  
3 Pole, 3 Wire, Non-Grounding**




**HBL9965C**

For Replacement Use Only

**IP20**  
SUITABILITY



**20A 250V**  
Non-NEMA  
Not UL Listed



**20A 125/250V**  
Non-NEMA  
Not UL Listed

## Plugs

Description	Cord Dia.	Catalog Number	
Black and white nylon.	.360"-.930" (9-24)	<b>HBL9965GCB</b>	<b>HBL9965C</b>
Corrosion resistant, yellow nylon.	.360"-.930" (9-24)	-	<b>HBL99CM65C</b>

Note: See page B-52 for accessories.



**HBL3325C**

## Flanged Inlets

Description	Catalog Number
Nylon casing, back wired.	- <b>HBL3325C</b>


Note: See page B-52 for accessories.




**HBL7411C**

For Replacement Use Only

**IP20**  
SUITABILITY



**20A 3Ø 250V AC**  
Non-NEMA  
Not UL Listed




**20A 3Ø Y**  
**120/208V AC**  
Non-NEMA  
Not UL Listed

## Plugs

Description	Cord Dia.	Catalog Number	
Black and white nylon.	.350"-1.150" (9-29)	<b>HBL7411GCB</b>	<b>HBL7411C</b>

Note: See page B-52 for accessories.



**HBL7408C**

## Flanged Inlets

Description	Catalog Number
Nylon casing, back wired.	- <b>HBL7408C</b>

Note: See page B-52 for accessories.

The devices shown on this page are not listed by Underwriters Laboratories Inc. and are for replacement use only in existing installations.

Dimensions in Inches (mm)

**CAUTION: To avoid electrical shock, review premises carefully and do not use if slot or blade configuration (design) is already in a circuit having a rating differing from the rating of this device.**