

## 50 Amp, 250 Volts DC and 600 Volts AC

### Plugs

Description	Cord Dia.	Catalog Number	
Nylon cover, thermoplastic polyester interior.	.830"-1.250" (21.08-31.75)	<b>HBL3765C</b>	<b>HBL7765C</b>

Note: See page B-60 for accessories.



**HBL3765C**

### Flanged Inlets

Description	Catalog Number
Zinc plated steel casing, thermoset interior.	<b>HBL3775</b> <b>HBL7958</b>
Zinc plated steel casing, thermoset interior with lift cover.	<b>HBL3768</b> <b>HBL7968</b>



**HBL3775**

### Connector Bodies

Description	Cord Dia.	Catalog Number	
Nylon cover, thermoplastic polyester interior.	.830"-1.250" (21.08-31.75)	<b>HBL3764C</b>	<b>HBL7764C</b>

Note: See page B-60 for accessories.



**HBL3768**


### Receptacles

Description	Catalog Number
Black phenolic.	<b>HBL3769</b> <b>HBL7379</b>

Note: See page B-60 for accessories.



**HBL3764C**



**HBL3769**

**Important Note:** Catalog numbers HBL7765C, HBL7958, HBL7968, HBL7764C, HBL7379 are for replacement use only. See other singly rated 50A Twist-Lock® devices in this section. HBL3700 series Twist-Lock devices do not interchange with any other devices in this section.

Dimensions in Inches (mm)