

## Watertight Safety-Shroud® Twist-Lock® Devices



	NEMA Rating Color Coded by Voltage	Plug/ Connector	Poles/Wires	Plug	Connector	Flanged Inlet	Receptacle
20 Amp	NEMA L5-20 20A 125V		2P/3W	<b>HBL2311SW</b>	<b>HBL2313SW</b>	<b>HBL2315SW</b>	<b>HBL2310SW</b>
	NEMA L6-20 20A 250V		2P/3W	<b>HBL2321SW</b>	<b>HBL2323SW</b>	<b>HBL2325SW</b>	<b>HBL2320SW</b>
	NEMA L7-20 20A 277V AC		2P/3W	<b>HBL2331SW</b>	<b>HBL2333SW</b>	<b>HBL2335SW</b>	<b>HBL2330SW</b>
	NEMA L14-20 20A 125/250V AC		3P/4W	<b>HBL2411SW</b>	<b>HBL2413SW</b>	<b>HBL2415SW</b>	<b>HBL2410SW</b>
	NEMA L15-20 20A 3Ø 250V AC		3P/4W	<b>HBL2421SW</b>	<b>HBL2423SW</b>	<b>HBL2425SW</b>	<b>HBL2420SW</b>
	NEMA L16-20 20A 3Ø 480V AC		3P/4W	<b>HBL2431SW</b>	<b>HBL2433SW</b>	<b>HBL2435SW</b>	<b>HBL2430SW</b>
	NEMA L21-20 20A 3ØY 120/208V AC		4P/5W	<b>HBL2511SW</b>	<b>HBL2513SW</b>	<b>HBL2515SW</b>	<b>HBL2510SW</b>
30 Amp	NEMA L5-30 30A 125V		2P/3W	<b>HBL2611SW</b>	<b>HBL2613SW</b>	<b>HBL2615SW</b>	<b>HBL2610SW</b>
	NEMA L6-30 30A 250V		2P/3W	<b>HBL2621SW</b>	<b>HBL2623SW</b>	<b>HBL2625SW</b>	<b>HBL2620SW</b>
	NEMA L14-30 30A 125/250V AC		3P/4W	<b>HBL2711SW</b>	<b>HBL2713SW</b>	<b>HBL2715SW</b>	<b>HBL2710SW</b>
	NEMA L15-30 30A 3Ø 250V AC		3P/4W	<b>HBL2721SW</b>	<b>HBL2723SW</b>	<b>HBL2725SW</b>	<b>HBL2720SW</b>
	NEMA L16-30 30A 3Ø 480V AC		3P/4W	<b>HBL2731SW</b>	<b>HBL2733SW</b>	<b>HBL2735SW</b>	<b>HBL2730SW</b>
	NEMA L17-30 30A 3Ø 600V AC		3P/4W	<b>HBL2741SW</b>	<b>HBL2743SW</b>	<b>HBL2745SW</b>	<b>HBL2740SW</b>
	NEMA L21-30 30A 3ØY 120/208V AC		4P/5W	<b>HBL2811SW</b>	<b>HBL2813SW</b>	<b>HBL2815SW</b>	<b>HBL2810SW</b>

## Mechanical Interlock Switched Safety Enclosure

Description	Catalog Number
Unfused mechanical interlock integrates a watertight safety shroud receptacle with a linked disconnect switch. See page B-41 for additional information.	<b>HBLMITL</b>



**HBLMITL**

## Specifications

Listings	
Listed to UL Standard 498 Certified to CSA Standard No.42 Fed. Spec. WC-596	
Environmental	
Moisture Resistance	UL Type 4, 4X, 12, IP66 suitability
Flammability (Enclosure)	V0 per UL94 or CSA 22.2 No. 0.17
Operating Temperatures	Maximum Continuous 75°C; Minimum -40°C (without impact)