





## Straight Blade Devices

**2 Pole, 3 Wire Grounding**

15 and 20 Ampere, 125 Volts

**ERGO™ Grip Plugs and Connector Bodies****HBL5565EY****HBL5565EBK****HBL8565E****HBL5569EY****HBL8569E****IP20**  
SUITABILITYNEMA 5-15P  
15A 125V  
UL CSA  
0.5 HPNEMA 5-20P  
20A 125V  
UL CSA  
1 HP**ERGO™ Grip Plugs**

Description	Cord Dia.	Catalog Numbers	
Overmolded yellow nylon.	.220"-.600" (5.6-15.25)	<b>HBL5565EY</b>	<b>HBL5585EY</b>
Overmolded black nylon.	.220"-.600" (5.6-15.25)	<b>HBL5565EBK</b>	<b>HBL5585EBK</b>

**ERGO™ Grip Hospital Grade Plugs**

Description	Cord Dia.	Catalog Numbers	
Overmolded white nylon.	.300"-.600" (7.6-15.25)	<b>HBL8565E</b>	<b>HBL8586E</b>

*Note: Horsepower ratings listed are AC only.***IP20**  
SUITABILITYNEMA 5-15R  
15A 125V  
UL CSANEMA 5-20R  
20A 125V  
UL CSA**ERGO™ Grip Connector Bodies**

Description	Cord Dia.	Catalog Numbers	
Overmolded yellow nylon.	.220"-.600" (5.6-15.25)	<b>HBL5569EY</b>	<b>HBL5589EY</b>
Overmolded black nylon.	.220"-.600" (5.6-15.25)	<b>HBL5569EBK</b>	<b>HBL5589EBK</b>

**ERGO™ Grip Hospital Grade Connector Bodies**

Description	Cord Dia.	Catalog Numbers	
Overmolded white nylon.	.300"-.600" (7.62-15.25)	<b>HBL8569E</b>	<b>HBL8589E</b>

*Notes: Connector bodies are not HP rated.***Accessories**

PLUGOUT® lockout device for Hubbell plugs and others.

**HLD**