

## Straight Blade Devices

### 2 Pole, 3 Wire Grounding


15 and 20 Ampere, 250 Volts  
Plugs and Flanged Inlets



HBL5666C




HBL5666CA



HBL5566EY



HBL5666VY



HBL5678C



NEMA 6-15P  
15A 250V  
UL CSA  
1.5 HP



NEMA 6-20P  
20A 250V  
UL CSA  
2 HP

### 15 and 20A Plugs

Description	Cord Dia.	Catalog Numbers	
Insulgrip® plug, black and white nylon.	.230"-.720" (5.8-18.3)	HBL5666C	HBL5466C
Insulgrip® plug, corrosion resistant, yellow nylon.	.230"-.720" (5.8-18.3)	HBL56CM66C	HBL54CM66C
8-Position Insulgrip angle plug, black and white nylon.	.325"-.655" (8.3-16.6)	HBL5666CA	HBL5466CA
ERGO™ Grip plug, overmolded yellow nylon.	.220"-.600" (5.6-15.25)	HBL5566EY	HBL5576EY
Valise® plug, yellow nylon.	.220"-.660" (5.6-16.8)	HBL5666VY	HBL5464VY

### ERGO™ Grip Hospital Grade Plugs

Description	Cord Dia.	Catalog Numbers	
Overmolded white nylon.	.300"-.600" (7.6-15.25)	HBL8566E	HBL8576E

### Valise Hospital Grade Plugs

Description	Cord Dia.	Catalog Numbers	
Valise plug, white nylon.	.300"-.660" (7.6-16.8)	HBL8666V	HBL8464V

Note: HP rating listed above are based on 208 to 240V AC only.

### Insulgrip Flanged Inlets

Description	Catalog Numbers	
Nylon casing, back wired.	HBL5678C	HBL5478C

Note: Flanged inlets are not HP rated.