

TWIST-LOCK® Devices

Accessories

for 20 and 30 Ampere 3, 4 and 5 Wire Receptacles and Flanged Devices



S720



Single-Gang Wall Plates

Rec. Plate
1.60" (40.64) Dia.

Description	Catalog Numbers
Black nylon, smooth.	P720B
Stainless steel 302/304, smooth.	S720
Brass, smooth.	B720



HBL7425WOA

Weatherproof Plates IP44 SUITABILITY

Description	Catalog Numbers
Cast aluminum, for FS/FD box mounting.	HBL7420
Gray thermoplastic, for FS/FD box mounting, corrosion resistant.	HBL7425WOA
Same as above except yellow.	HBL74CM25WOA



WP2

Weatherproof Plate for Flanged Inlets and Flanged Receptacles IP44 SUITABILITY

Description	Catalog Number
Gray thermoplastic, corrosion resistant.	WP2

Notes: Weatherproof plates are UL Listed for wet and damp location with cover closed. Those with suffix WOA are UL Listed with cover open.

Closure Cover for 3 Wire Flanged Inlets

Description	Catalog Number
Rubber closure plug.	HBL2899

Note: Closure cover not UL Listed. Not CSA Certified.



HBL2899

Closure Cover for 4 Wire Flanged Inlets

Description	Catalog Number
Rubber closure plug.	HBL2898

Note: Closure cover not UL Listed. Not CSA Certified.