

## Marine Products

**Internationally Rated**

16, 32 Ampere, 230 Volt

**Ship-to-Shore Power System**

Hubbell offers the only CE certified electrical shore power system truly dedicated for boats destined for Europe and the International community. Hubbell's offering of international shore power inlets is available in stylized #316 Type Stainless Steel as well as attractive white non-metallic types resembling our domestic offering in style and appearance but are not interchangeable with the domestic shore power system.

Utilizing standard NEMA (National Electrical Manufacturer's Association) configurations not typically used in the marine market, Hubbell can offer a safe and non-interchangeable 16 Amp 230 Volt system and 32 Amp 230 Volt system for use with 50 cycle systems. The system includes white power supply cables (one-end, female only) in both the 16 Amp and 32 Amp categories.

**IP56**

SUITABILITY

**16 Amp 230 Volt  
Ship-To-Shore Power System**

Description	Catalog Numbers
Non-metallic, white, stylized, U.V. resistant shore power inlet. White Centrex cover makes the inlet weatherproof when closed. Mounting holes are 2 3/8" (60.3) on centers and match most existing mounting patterns. Rear enclosure strain/relief cap is provided.	<b>HBL316NM</b>
Traditional, stainless steel shore power inlet has new easy-to-wire terminations. Interior is transparent for quick and easy visual inspection. Interior is shielded from the elements by a gasketed, self-closing cover, watertight when cover is screwed in place. Mounting holes are 2 3/8" (60.3) on centers. Mounting screws and gasket included. Protective rear enclosure/strain relief also included.	<b>HBL316SSX</b>
25' (7.6m) white, vinyl jacketed power supply cord with female (boat side) end only; other end blunt cut.	<b>HBL316CSW25</b>
50' (15.2m) white, vinyl jacketed power supply cord with female (boat side) end only; other end blunt cut.	<b>HBL316CSW</b>
Yellow locking connector replacement end for #HBL316CSW25 & #HBL316CSW.	<b>HBL316CRC</b>
White Seal-Tite cover with threaded sealing ring for use with #HBL316CRC and #HBL332CRC connector bodies.	<b>HBL103RX</b>

**32 Amp 230 Volt, 50 Cycle Ship-To-Shore Power System**

Description	Catalog Numbers
Non-metallic, white, stylized, U.V. resistant shore power inlet. White Centrex cover makes the inlet weatherproof when closed. Mounting holes are 2 3/8" (60.3) on centers and match most existing mounting patterns. Rear enclosure/strain relief cap is provided.	<b>HBL332NM</b>
Traditional, stainless steel shore power inlet has new easy-to-wire terminations. Interior is transparent for quick and easy visual inspection. Interior is shielded from the elements by a gasketed, self-closing cover, watertight when cover is screwed in place. Mounting holes are 2 3/8" (60.3) on centers. Mounting screws and gasket included. Protective rear enclosure/strain relief also included.	<b>HBL332SSX</b>
50 ft. (15.2m) white, vinyl jacketed power supply cord with female (boat side) end only; other end blunt cut.	<b>HBL332CSW</b>
Yellow locking connector replacement end for #HBL332CSW.	<b>HBL332CRC</b>
White Seal-Tite cover with threaded sealing ring for use with #HBL316CRC and #HBL332CRC connector bodies.	<b>HBL103RX</b>



**HBL316NM**  
**HBL332NM**



**HBL316SSX**  
**HBL332SSX**



**HBL316CSW25**  
**HBL316CSW**  
**HBL332CSW**



**HBL316CRC**  
**HBL332CRC**



**HBL103RX**