

Straight Blade Devices

2 Pole, 3 Wire Grounding

15 and 20 Ampere, 250 Volts

Heavy Duty, Specification Grade Receptacles



NEMA 6-15R
15A 250V
UL CSA
1.5 HP



NEMA 6-20R
20A 250V
UL
2 HP

Heavy Duty, Specification Grade, Duplex Receptacles

Description	Color	Catalog Numbers	
Flush, nylon face, back & side wired.	Brown	HBL5662	HBL5462
	Ivory	HBL5662I	HBL5462I
	Gray	-	HBL5462GY
Flush, nylon face, back & side wired, Robertson/slotted screws.	Brown	HBL5662CN	HBL6392CN*
	Ivory	HBL5662ICN	-
Isolated Ground.	Orange	IG5662	IG5462

*Cat. No. 6392CN is UL/CSA listed and has a 20A 250V configuration only.

Heavy Duty, Hospital Grade, Duplex Receptacles

Description	Color	Catalog Numbers	
Flush, thermoplastic polyester face.	Brown	HBL8600	HBL8400
	Ivory	HBL8600I	HBL8400I

Heavy Duty, Specification Grade, Single Receptacles

Description	Color	Catalog Numbers	
Flush, nylon face, back & side wired.	Brown	HBL5661*	HBL5461
	Ivory	HBL5661I*	HBL5461I
Isolated Ground.	Orange	IG5661	IG5461
Panel mount 1.94" (49.3) centers.	Brown	HBL5684	-
Flush, nylon face, back & side wired, Robertson/slotted screws.	Brown	-	HBL6391CN**
	Ivory	-	HBL6391ICN**

*Add "CN" suffix for Robertson/slotted mounting and terminal screws. All others have slotted screws.

**Products are UL/CSA listed and have 20A, 250V configuration only.

Compact, Specification Grade, Duplex and Panel Mount Single Receptacles

Description	Color	Catalog Numbers	
Flush, nylon face, side wired only,	Brown	HBL5652	-
	Ivory	HBL5652I	-
Panel mount 1.75" (44.5) centers.	Brown	HBL5658	-

Notes: HP ratings are AC only.

See page A-42 for accessories.

See Section G for full line of Circuit Guard® isolated ground devices.

