

# Temporary Power Distribution Systems

## Cable Sets and Receptacles

### Replacement Parts and Specifications

#### Cable Sets and Receptacles

Description	Catalog Numbers
50A pre-wired wall mounted receptacle, with 2 ft. wire leads.	SR50
50A cord set- 50 ft. cable (input/output).	SCB50
60A cord set- 6 ft. cable (input/output).	SCC06
60A cord set- 50 ft. cable (input/output).	SCC50
60A, 3Ø 120/208V Pin and Sleeve wall mounted receptacle.	HBL560R9W
1¼" hub 15 deg. non-metallic angle back box for 60A receptacle.	BB601W
1½" hub 15 deg. metallic 4-way angle back box for 60A receptacle.	FW60100

Note: Consult factory for alternate cable lengths.



HBL2310SW

#### Replacement Parts

Description	Catalog Numbers
20A, 125V straight blade receptacle.	HBL53R61
20A, 125V Safety-Shroud Twist-Lock® receptacle.	HBL2310SW
30A, 250V Safety-Shroud Twist-Lock® receptacle.	HBL2620SW
30A, Reverse Service Safety-Shroud connector.	HBL2713SR
30A, Reverse Service inlet.	HBL2715SWR
50A, 125/250V Twist-Lock® receptacle.	CS6369
50A, 125/250V Twist-Lock® inlet.	HBL6375S
60A, 3Ø 120/208V Pin and Sleeve reversed service receptacle (inlet).	HBL560B9R
60A, 3Ø 120/208V Pin and Sleeve receptacle (outlet).	HBL560R9W
60A, 3Ø 120/208V Pin and Sleeve reversed service plug (female).	HBL560P9WR
60A, 3Ø 120/208V Pin and Sleeve plug (male).	HBL560P9W
GFCI module.	GFM20
50A Spider supervisory kit.	SSK
60A Spider supervisory kit.	SSK60
Spider circuit breaker cover.	SCBC
Spider leg kit.	SLK
Spider leg kit, green.	SLKG
50A receptacle cover plate.	HBL77CM74WO



GFM20



SSK

#### Specifications

##### Spider® II

<b>Listing Certification</b>	UL 1640 cUL and CSA, UL 943.
<b>Environment</b>	Indoor and outdoor wet and dry locations.
<b>Enclosure Type</b>	3R, rainproof, suitable for use in damp locations.
<b>Code Compliance</b>	NEC®, ANSI/NFPA 70.



SCBC



SCB50



SR50



HBL2713SR



HBL77CM74WO