


**H320R**




**Receptacle IEC 320 Compatible**



| Description                        | Catalog Number  |
|------------------------------------|-----------------|
| 20/16A 250V AC IEC straight blade. | <b>H320R</b>    |
| For Ring Terminal connection.      | <b>H320RRT*</b> |

Note: \*Not UL Listed.



**H320C**




**Connector**

**IP20**  
SUITABILITY



| Description                        | Catalog Number |
|------------------------------------|----------------|
| 20/16A 250V AC IEC straight blade. | <b>H320C</b>   |



**H320P**




**Plug IEC 320 Compatible**

**IP20**  
SUITABILITY




| Description                        | Catalog Number |
|------------------------------------|----------------|
| 20/16A 250V AC IEC straight blade. | <b>H320P</b>   |



**H320B**




**Inlets**



| Description   | Catalog Number |
|---|----------------|
| 20/16A 250V AC IEC straight blade.                      | <b>H320B</b>   |
| 20/16A 250V AC IEC straight blade with retention clamp. | <b>H320BL</b>  |

Note: See page A-67 for technical information.



**H320BL**

Dimensions in Inches (mm)



**IEC 320 Devices**

**Specifications**

|                        |  |
|------------------------|--|
| <b>Receptacle</b>      |  |
| Catalog Number         | H320R  |
| Description            | IEC Configuration compatible straight blade panel mount receptacle.  |
| Type                   | 2 Pole + earth.  |
| Rating                 | 16A 250V AC for European service;<br>20A 250V AC for North American service.   |
| Certification          | UL Listed 20A 250V AC – File No. E2186;<br>CSA Certified 20A 250V AC – File No. 17337.   |
| Terminal Accommodation | North American – #16-12 AWG stranded or solid copper conductor only.<br>International – 1.55mm <sup>2</sup> –2.5mm <sup>2</sup> .  |
| <b>Connector</b>       |  |
| Catalog Number         | H320C  |
| Description            | IEC Detachable straight blade connector.   |
| Type                   | 2 Pole + earth.  |
| Rating                 | 16A 250V AC for European service;<br>20A 250V AC for North American service.   |
| Configuration          | IEC 60320-1 Style appliance coupler, C19.  |
| Certification          | UL Listed 20A 250V AC – File No. E1706;<br>CSA Certified 20A 250V AC – File No. 17337;<br>UL Classified to IEC 320, 16A 250V AC – File No. E111246;  |
| Cord Accommodation     | North American – 16/3SJ-12/3SJ (.325–.475 in. dia.);<br>International – (HAR cord) 3x1.5mm <sup>2</sup> –3x2.5mm <sup>2</sup> (8mm–12mm dia.).   |
| IP Suitability         | IP20.  |
| <b>Plug</b>            |  |
| Catalog Number         | H320P  |
| Description            | IEC Configuration compatible straight blade Valise® plug.  |
| Type                   | 2 Pole + earth.  |
| Rating                 | 16A 250V AC for European service;<br>20A 250V AC for North American service.   |
| Certification          | UL Listed 20A 250V AC – File No. E1706;<br>CSA Certified 20A 250V AC – File No. 17337.   |
| Cord Accommodation     | North American – 16/3 SJ-12/3SJ (.325–.475 in. dia.);<br>International – (HAR cord) 3x1.5mm <sup>2</sup> 3x2.5mm <sup>2</sup> (8–12mm dia.).   |
| IP Suitability         | IP20.  |
| <b>Inlet</b>           |  |
| Catalog Number         | H320B and H320BL   |
| Description            | IEC Straight blade panel mount power inlet.  |
| Type                   | 2 Pole + earth.  |
| Rating                 | 16A 250V AC for European service;<br>20A 250V AC for North American service.   |
| Configuration          | IEC 60320-1 Style appliance coupler, C20.  |
| Certification          | UL Listed 20A 250V AC – File No. E1706;<br>CSA Certified 20A 250V AC – File No. 17337;<br>UL Classified to IEC 320, 16A 250V AC – File No. E111246;  |
| Terminal Accommodation | VDE Certified at 16A 250V AC – File No. 12469 1550 1002.<br>North American – #16-12 AWG stranded or solid copper conductor only.<br>International – 1.5mm <sup>2</sup> –2.5mm <sup>2</sup> . |