




30A 125V
 NEMA L5-30R
 UL/CSA
 2 HP



30A 250V
 NEMA L6-30R
 UL/CSA
 2 HP



30A 277V AC
 NEMA L7-30R
 UL/CSA
 3 HP

Connector Bodies

Watertight Safety-Shroud®

IP66 SUITABILITY UL Type 4x, 12

| Description | Cord Dia. | Catalog Number | | |
|--|-----------------------|------------------|------------------|---|
| Black Valox® housing, white Valox® clamps. | .360"-.930" (9-24) | HBL2613SW | HBL2623SW | - |
| Reverse service, black Valox® housing, white Valox® clamps (use with HBL2615SWR), (Not shown). | .360"-.930" (9-24) | HBL2613SR | - | - |

Insulgrip®

IP20 SUITABILITY

| Description | Cord Dia. | Catalog Number | | |
|---|-----------------------|------------------|------------------|----------------|
| Black and white nylon. | .360"-.930" (9-24) | HBL2613 | HBL2623 | HBL2633 |
| Heat stabilized, gray nylon, 220° F (104° C). | .360"-.930" (9-24) | HBL2613F | HBL2623F | - |
| Corrosion resistant, yellow nylon. | .360"-.930" (9-24) | HBL26CM13 | HBL26CM23 | - |
| All black nylon. | .360"-.930" (9-24) | HBL2613BK | HBL2623BK | - |

Note: See page B-51 for accessories.

Valise®

IP20 SUITABILITY

| Description | Cord Dia. | Catalog Number | | |
|------------------------------------|----------------------------|-------------------|-------------------|---|
| Yellow nylon. | .590"-.930" (15.0-23.6) | HBL2613VY | HBL2623VY | - |
| Corrosion resistant, yellow nylon. | .590"-.930" (15.0-23.6) | HBL26CM13V | - | - |
| Black nylon. | .590"-.930" (15.0-23.6) | HBL2613VBK | HBL2623VBK | - |

Note: See page B-51 for accessories.

Receptacles

Watertight Safety-Shroud®

IP66 SUITABILITY UL Type 4x, 12

| Description | Catalog Number | | |
|---|------------------|------------------|---|
| Gray Valox® housing and flange, back wired. | HBL2610SW | HBL2620SW | - |

Note: See page B-54 for accessories.

Safety-Shroud® Twist-Lock®

IP20 SUITABILITY

| Description | Catalog Number | | |
|---|-------------------|-------------------|---|
| Gray Valox® angle housing, one gang, back wired. | HBL2610AR | HBL2620AR | - |
| Gray Valox® surface mounting, one gang, back wired. | HBL2610SR | HBL2620SR | - |
| Gray Valox® semi-flush, two gang, back wired. | HBL2610SR2 | HBL2620SR2 | - |

Note: See page B-54 for accessories.

Single Flush Receptacles

IP20 SUITABILITY

| Description | Catalog Number | | |
|--|------------------|------------------|----------------|
| Black nylon face, back and side wired. | HBL2610 | HBL2620 | HBL2630 |
| Blue nylon face, back and side wired. | HBL2610M6 | HBL2620M6 | - |
| Isolated ground, orange nylon face, back and side wired. | IG2610 | IG2620 | - |
| Corrosion resistant, yellow nylon face, back and side wired. | HBL26CM10 | HBL26CM20 | - |
| Ring terminal connection. | HBL2610RT | HBL2620RT | - |

Note: See page B-50 for accessories.

Insulgrip® Flanged Receptacles


| Description | Catalog Number | | |
|---|-----------------|-----------------|----------------|
| Nylon casing, back wired. | HBL2616 | HBL2626 | HBL2636 |
| Heat stabilized, gray nylon, 220° F (104° C). | HBL2616F | HBL2626F | - |

Note: See page B-50 for accessories.


Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.




HBL2613SW




HBL2623




HBL2613VY



HBL2610SW



HBL2620AR



HBL2620SR

Dimensions in Inches (mm)