



HBL2751




HBL2755



HBL2753



HBL2750



HBL2756

**IP20**  
SUITABILITY



**30A 3ØY**  
**120/208V AC**  
NEMA L18-30P  
UL Listed  
3 HP



**30A 3ØY**  
**277/480V AC**  
NEMA L19-30P  
UL Listed  
10 HP



**30A 3ØY**  
**347/600V AC**  
NEMA L20-30P  
UL Listed

## Plugs

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	<b>HBL2751</b>	<b>HBL2761</b>	<b>HBL2771</b>

Note: See page B-53 for accessories.

## Flanged Inlets

Description	Catalog Number		
Nylon casing, back wired.	<b>HBL2755</b>	<b>HBL2765</b>	<b>HBL2775</b>

Note: See page B-52 for accessories.

**IP20**  
SUITABILITY



**30A 3ØY**  
**120/208V AC**  
NEMA L18-30R  
UL Listed  
3 HP



**30A 3ØY**  
**277/480V AC**  
NEMA L19-30R  
UL Listed  
10 HP



**30A 3ØY**  
**347/600V AC**  
NEMA L20-30R  
UL Listed

## Connector Bodies

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	<b>HBL2753</b>	<b>HBL2763</b>	<b>HBL2773</b>

Note: See page B-53 for accessories.

## Single Flush Receptacles

Description	Catalog Number		
Black nylon face, back and side wired.	<b>HBL2750</b>	<b>HBL2760</b>	<b>HBL2770</b>

Note: See page B-52 for accessories.

## Flanged Receptacles

Description	Catalog Number		
Nylon casing, back wired.	<b>HBL2756</b>	<b>HBL2766</b>	<b>HBL2776</b>

Note: See page B-52 for accessories.

See page B-69 for technical information on Twist-Lock devices.