



Meets UL Standards 1449 3rd Edition and 498; CSA Certified

Damage-alert alarm sounds when surge protection is no longer functioning and keeps sounding until the receptacle is replaced or muting screw is utilized

Muting screw allows damage-alert alarm to be silenced until device is replaced

Power-on indicator light verifies instantly that power is available at the receptacle and the suppression circuit is fully functional; light off means power has been interrupted; flashing light indicates surge protection circuitry has been damaged



Distinctive surge symbol provides quick visual identification of surge suppression receptacle. High-impact nylon face resists breakage

Fits standard wall box

Automatic self-grounding staple attached to bridge meets NEC® requirements

IG8362SA

Note: The effectiveness of SPD devices diminishes with the increase in distance between the device and the equipment to be protected.

Surge Protection Receptacles

Hubbell has the broadest offering of SPD receptacles in the industry with technology that is unsurpassed. Inside Hubbell SPD receptacles are two 22mm square MOVs providing 240 joules of surge protection for each mode. The nylon component shield protects the printed circuit

board from moisture and contaminants. An all-glass PC board provides superior moisture immunity for longer life in humid environments. Conformal coating is provided on the printed circuit board for additional moisture immunity.


NEC® is a registered trademark of the National Fire Protection Association (NFPA).




Circuit Guard®, Specification Grade Duplex Receptacles




Description	Color	Catalog Number	
Surge suppression receptacles with light, 240 joules/15000A per mode.	Blue	HBL5260SA	HBL5360SA
	Ivory	HBL5260ISA	HBL5360ISA
	Office White	HBL5260OWSA	HBL5360OWSA
	White	HBL5260WSA	HBL5360WSA
Surge suppression receptacles with light and alarm, 240 joules/15000A per mode.	Almond	HBL5262ALSA	HBL5362ALSA
	Blue	HBL5262SA	HBL5362SA
	Gray	HBL5262GYSA	HBL5362GYSA
	Ivory	HBL5262ISA	HBL5362ISA
	Office White	HBL5262OWSA	HBL5362OWSA
	White	HBL5262WSA	HBL5362WSA
Isolated ground, surge suppression receptacles with light and alarm, 240 joules/15000A per mode.	Blue	IG5262SA	IG5362SA
	Gray	IG5262GYSA	IG5362GYSA
	Ivory	IG5262ISA	IG5362ISA
	Office White	IG5262OWSA	IG5362OWSA
	Orange	IG5262OSA	IG5362OSA
	White	IG5262WSA	IG5362WSA
4-PLEX® surge suppression receptacles with lights. 80 joules/6500A per mode.	Blue	HBL415S	HBL420S
	Ivory	HBL415IS	HBL420IS



HBL5262GYSA



IG5362SA



HBL8362ISA

Circuit Guard®, Hospital Grade Duplex Receptacles


Description	Color	Catalog Number	
Surge suppression receptacles with light and alarm, 240 joules/15000A per mode.	Almond	HBL8262ALSA	HBL8362ALSA
	Blue	HBL8262SA	HBL8362SA
	Gray	HBL8262GYSA	HBL8362GYSA
	Ivory	HBL8262ISA	HBL8362ISA
	Red	HBL8262RSA	HBL8362RSA
	White	HBL8262WSA	HBL8362WSA
Isolated ground, surge suppression receptacles with light and alarm, 240 joules/15000A per mode.	Blue	IG8262SA	IG8362SA
	Gray	IG8262GYSA	IG8362GYSA
	Ivory	IG8262ISA	IG8362ISA
	Orange	IG8262OSA	IG8362OSA
	Red	IG8262RSA	IG8362RSA
	White	IG8262WSA	IG8362WSA
4-PLEX surge suppression receptacles with lights, 80 joules/6500A per mode.	Blue	—	HBL420HS
	Ivory	—	HBL420HIS
	Red	—	HBL420HRS

4-PLEX® Accessories


Description	Color	Catalog Number
4-PLEX adapter plates for 1- and 2-gang (4-PLEX mount directly to 4" (101.6) square device boxes).	Blue	HBL4APBL
	Ivory	HBL4API
	Red	HBL4APR
4-PLEX portable box. Portable 4" (101.6) square box with one cord grip. Accepts up to .66" (16.8) dia. cord.	Ivory	HBL4PBI

Note: 4-PLEX box is not UL Listed.

Wallplates (Sold Separately)

Configuration	High-Impact Nylon			Plated Steel	Stainless Steel (S/S) Brass		
	Color	Standard	Mid-Size				
 1-Gang	Almond	NP26AL	NPJ26AL	Chrome Brass Plated	SCH26 SBP26	Smooth S/S	SS26
	Blue	—	NPJ26CBL*			Smooth S/S	SSJ26^
	Blue	—	NPJ26BL			Smooth	SB26
	Gray	NP26GY	NPJ26GY				
	Ivory	—	NPJ26C*				
	Ivory	NP26I	NPJ26I				
	Off. White	NP26OW	NPJ26OW				
	Orange	NP26OIG**	—				
	Red	NP26R	NPJ26R				
	White	NP26W	NPJ26W				

Note: *Premarked "COMPUTER ONLY." Lettering is block 1/4" high.
 **Premarked "ISOLATED GROUND." Lettering is block 1/4" high.
 ^ Jumbo size plate.
 See section N for additional wallplates.
 See page M-19 for technical information.



HBL415S

Dimensions in Inches (mm)