

# TAPPING TEES CON'T

## DAA High Pressure Tapping Tees - DIP



The DAA is easy to assemble and delivers a high quality design for the gas and water industry.

Field of Application      Installation of service and branch pipes to PE 2406/2708 and 3408/4710

Range of Application      Gas up to 125 psi and water up to 200 psi

For higher pressure ranges, contact IPEX at 800-463-9572

- Hot tapping tee designed for leakproof installation under pressure up to 160 psi for water and 125 psi for gas
- Ease of assembly—no rounding clamps or special tools
- Cutter and sleeve made of brass
- Brass guide allows easy cutting of thick wall pipe
- Lower and upper "cutter stops" prevent overcutting as well as accidental removal of cutter
- Threaded plug with o-ring seal
- Corrosion-proof construction
- NSF-61



Nominal Pipe OD DIP	Nominal Outlet (in)	Product Code	ID	OD 1	OD 2	Cutter	L	Z1	Z2	B
4"	1/2" CTS	228251	4.512	0.626	1.969	1.201	4.764	2.905	4.016	4.785
4"	3/4" IPS	228252	4.512	1.051	1.969	1.201	4.764	2.846	4.409	4.764
4"	1" CTS	228250	4.512	1.126	1.969	1.201	4.764	2.846	4.527	4.785
4"	2" IPS	228253	4.512	2.378	1.969	1.201	4.780	2.913	7.086	4.905
6"	1/2" CTS	228254	6.638	0.626	1.969	1.201	6.575	4.500	4.586	7.677
6"	3/4" IPS	228255	6.638	1.051	1.969	1.201	6.575	4.528	4.331	7.677
6"	1" CTS	228256	6.638	1.126	1.969	1.201	6.575	4.528	4.331	7.677
6"	2" IPS	228257	6.638	2.378	1.969	1.201	6.575	4.803	6.811	7.677
8"	1/2" CTS	228258	8.605	0.626	1.969	1.201	6.575	5.483	4.586	7.677
8"	3/4" IPS	228259	8.605	1.051	1.969	1.201	6.575	5.315	4.331	7.677
8"	1" CTS	228260	8.605	1.126	1.969	1.201	6.575	5.315	4.331	7.677
8"	2" IPS	228261	8.605	2.378	1.969	1.201	6.575	5.827	6.811	7.677

FRIATEC Safety Fittings can be fused to all PE pipes SDR Range 11 through 17.6.  
Allow electrofusion joints to cool prior to handling, pressurizing or tapping.

## DAA Tapping Tee Accessories

Description	Product Code
10mm Hex Wrench for 1-1/4" Main DAA Tees	228050
17 mm Hex Wrench for 2" Main DAA Tees	228051
19mm Hex Wrench for 2" x 2" and 3" - 16" Main DAA Tees	228052
Friatop Pneumatic Top Loading Tool for 10" - 16" DAA-TL and all TL fittings	228053
Pressure Test Cap Adapter (optional) for DAA style 1-1/4" Tees	228024
Pressure Test Cap Adapter (optional) for DAA style 2" - 16" Tees	228055



## Tapping Tee Accessories

Description	Part No.
Low Volume Pressure Test Cap (stem sizes 1/2" to 1")	528039
Medium Volume Pressure Test Cap (stem size 1-1/4")	528040
2" IPS x 1/2" CTS Training Test Tee	228356
2" IPS x 3/4" IPS Training Test Tee	228357
2" IPS x 1" CTS Training Test Tee	528043
Tapping Tool	528038