DRAINWAY ABS DWV SYSTEMS

ABS-DWV

Throughout Canada, ABS-DWV (drain, waste and vent) piping has been successfully used in single family homes and general wood-frame construction. Builders and contractors have enjoyed the durability, ease of installation and overall value of ABS in providing a plumbing drain system.

The pipe may be used both above ground and underground and is made in Schedule 40 pipe dimensions in either sold wall or cell core composition. Sizes range from 1-1/4" - 6" (32mm to 150mm) and a broad range of ABS DWV fittings are also provided by IPEX for complete system installations.

APPLICATIONS

Drain Waste and Vent Piping for:

- Single Family Homes
- Multi-Plex Residential
- General Wood Frame Buildings

STANDARDS



Solid Wall CSA B181.1

Cell Core ASTM F628

DID YOU KNOW?

ABS is commonly used by the automotive industry for car bumpers due to its affordable cost, high impact strength and general toughness.

ADVANTAGES

Years of Maintenance-Free Service

ABS will not rust, pit or degrade when exposed to moisture and is extremely resilient and durable. This lightweight ABS-DWV offers easy and quick installation without specialized equipment, even in confined spaces.

Code Compliant

IPEX ABS (Solid Wall) and fittings have been third-party certified to CSA B181.1 while ABS (Cell Core) pipe is certified to ASTM F628, both ensuring a consistent quality product with reliable long-term performance. In addition, IPEX can be of assistance in suggesting where ABS piping is permitted by Building codes and or where other products may be a more suitable alternative.

Complete Line of Fittings

IPEX manufacturers not only ABS-DWV pipe, but a complete line of ABS fittings, ensuring integrity throughout the plumbing system. In addition, our products are promptly available throughout any IPEX distributor.

2

3

PRODUCT SELECTION CHART

	Dimension Product				Dimension Product		
	inches	mm	Product Code		inches	mm	Product Code
Male Trap Adapt	er Sp x Plasti	c Nut		Adjustable Offset Closet Flange H			
	1-1/4	32	027476	(CARA)	4 x 3	100 x 75	027574
	1-1/2	40	027477				
	1-1/2 x 1-1/4	40 x 32	027478				
	1-1/2 x 7 Long	40 x 175 Long	027651				
	2	50	027302	45º Disabarra	Cleast Flance		
				45° Discharge		100 x 75	-
Female Trap Ada	pter Plastic I	Nut x H			4 x 3	100 x 75	027950
	1-1/4	32	027320				
	1-1/2	40	027321	<u> </u>			
	1-1/2 x 1-1/4	40 x 32	027329				
				Adjustable Clos	set Flange H		
Closet Flange	4				4 x 3	100 x 75	027586
	4 x 3	100 x 75	027584				
	4 x 4	100 x 100	027573				
				Adjustable Closet Flange with Test Plug			
					4 x 3	100 x 75	027588
Adjustable Close	et Flange Flus	hFit ⊢					
65-30	4 x 3	100 x 75	027582	<u> </u>			
<u> </u>				Adjustable Clos	-		Non-CSA)
Closet Flange wi	ith Test Plug	Н			4 x 3	100 x 75	027590
0	4 x 3	100 x 75	027591				
				Adjustable Clos	ot Flanga		
				Aujustable 6103	4 x 3	100 x 75	027587
					4 X S	100 x 75	027587
Adjustable Close	-	-		\bigcirc			
	4 x 3	100 x 75	027583				
				Closet Flange S	Snacer Ring		
				oroset mange e	4 x 3	100 x 75	027002
Closet Flange	Sp				4 × 3	100 x 7 5	027002
oroseerrange	4 x 3	100 x 75	027585				
	4 X 3	100 x 7 5	027303				
\bigcirc				Reducing Adap	ter (Sewer to	DWV) SpxH	
					4 x 3	100 x 75	027294
Adjustable Close	et Flange Kit fo	or Concrete			4 x 4	100 x 100	027050
(Č)	4 x 3	100 x 75	027592				
				Poducing Adopt			
				Reducing Adapt			007000
					4 x 3	100 x 75	027286
				(((((((
Adjustable Close	et Flange Kit fo	or Concrete					
	for use in Slab	on Grade W.C. I	nstallations	Unb Adaptar (1111	
	4 x 3	100 x 75	027593	Hub Adapter (Sewer to DWV)		007075
\square	-				4 x 3	100 x 75	027376
\bigcirc				((()))			

25