

# SYSTEM XFR DRAINAGE SYSTEMS

1-1/2" - 12" (40mm - 300mm)

## SYSTEM XFR® DWV

Contractors installing DWV pipe in high buildings and plenums had few alternatives to heavy cast iron and copper. IPEX has changed that. System XFR® is the world's first PVC DWV system rated for high buildings and air plenums where the National Building Code mandates more stringent Flame Spread and Smoke Development requirements which previously limited the use of thermoplastic.

Suitable for use in noncombustible environments, System XFR's advanced material has a Flame Spread Rating of 25 and Smoke Developed Classification of 50 which permits it to be installed in High Buildings and Air Return Plenums in accordance with local Codes.

And in addition to its flame and smoke attributes, System XFR delivers all the performance advantages you'd expect from thermoplastic piping.

### APPLICATIONS

Drain Waste and Vent Piping in:

- Commercial
- Industrial
- Residential
- Above ground or underground

### STANDARDS



CSA B181.2  
CAN/ULC S102.2

### ADVANTAGES

#### 1 Flame & Smoke

System XFR possesses superior fire- and smoke- retardant capabilities. When tested to the CAN/ULC S102.2 Standard, System XFR achieved a Flame Spread Rating of not greater than 25 and a Smoke Developed Classification of not greater than 50.

#### 2 Code Compliance

Ideal for noncombustible applications, System XFR meets these national and provincial building codes:

- High buildings as defined by NBC article 3.2.6
- Air plenums as defined by NBC article 3.6.4.3
- Noncombustible construction as defined by NBC article 3.1.5
- Penetrating a rated fire separation as defined by NBC article 3.1.9.4.(4)

#### 3 High Impact Resistance

Thanks to its advanced materials, System XFR demonstrates a high impact strength in cold temperatures. Impact-tested at 0 °C and 23 °C, XFR is tough enough to exceed the CSA requirements.

#### 4 Improved Flow

System XFR has a substantially lower roughness factor compared to metal systems, allowing for overall improved flow. It's also made with a larger inside diameter which provides a greater cross-sectional area for flow and raises both carrying capacity and flow rates. This feature gives engineers the versatility to design smaller, compact systems that can still handle the necessary flow rates.

#### 5 Lower Thermal Conductivity

System XFR sweats less than metal pipe due to its excellent insulating properties. As a result, XFR can reduce — and in many cases, eliminate — the need for insulation.

#### 6 Comparable Noise Attenuation

In real world sound tests performed on constructed buildings, IPEX DWV systems have proven to provide comparable noise attenuation when compared to cast iron from drainage flow. Numerous installations from schools to hospitals and nursing homes have been plumbed with these IPEX drainage systems, all proving that in these critical installations the IPEX systems measure up in terms of sound transfer.





## DID YOU KNOW?

**SYSTEM XFR** — the world’s first uncoated PVC rated for high buildings and plenums where tighter fire and smoke regulations have previously limited the use of thermoplastic.

Suitable for use in noncombustible environments, System XFR’s advanced material meets all fire-resistance and smoke development codes. Its revolutionary fire-retardant properties virtually eliminate flame spread and reduce the volume of smoke generated.

### SHORT FORM SPECIFICATIONS

#### SYSTEM XFR DWV PIPE AND FITTINGS

IPEX System XFR Drain, Waste and Vent pipe and fittings shall be certified to CSA B181.2 and when used in noncombustible construction, high buildings and air plenums, they shall be tested and listed in accordance with CAN/ULC S102.2 and clearly marked with the certification logo indicating a Flame Spread Rating not more than 25 and a Smoke Developed Classification not exceeding 50.

System XFR® pipe and fittings have been tested and certified by CSA to the CSA B181.2 standard. System XFR pipe and fittings are listed with ITS (Warnock Hersey) to exhibit Flame and Smoke values as per CAN/ULC S102.2-10.

#### Test Results

ITS (Warnock Hersey) conducted the testing in accordance with CAN/ULC S102.2 test standard. The following table summarizes the results of these tests.

Component	Flame Spread Rating	Smoke-Developed Classification
<b>System XFR®</b>		
Pipe	≤ 25	≤ 50
Fittings	≤ 25	≤ 50
Fabricated PVC fittings with XFR Coating	≤ 25	≤ 50

## PRODUCT SELECTION CHART - SYSTEM XFR

	Dimension		Product Code
	inches	mm	

### 45° Wye H x H x H




1-1/2	40	526171
2	50	526172
2 x 1-1/2 x 1-1/2	50 x 40 x 40	526194
2 x 1-1/2	50 x 40	526195
3	75	526173
3 x 1-1/2	75 x 40	526201
3 x 2	75 x 50	526196
4	100	526174
4 x 2	100 x 50	526198
4 x 3	100 x 75	526197
6	150	526175
6 x 4	150 x 100	526199
8	200	526560
8 x 4	200 x 100	526606
8 x 6	200 x 150	526607
10	250	526706
10 x 4	250 x 100	526703
10 x 6	250 x 150	526704
10 x 8	250 x 200	526705
12	300	526711
12 x 4	300 x 100	526707
12 x 6	300 x 150	526708
12 x 8	300 x 200	526709
12 x 10	300 x 250	526710
14 x 4	350 x 100	526712
14 x 6	350 x 150	526713
16 x 4	400 x 100	526718
16 x 6	100 x 150	526719
18 x 4	450 x 100	526725
18 x 6	450 x 150	526726

### 45° Wye Sp x H x H



3	75	426635
3 x 1-1/2	75 x 40	426638


### 45° Wye Sp x Sp x H



			FOR USE WITH <b>MJ GREY™</b>
8 x 4	200 x 100	526985	
8 x 6	200 x 150	526986	
10 x 4	250 x 100	526988	
10 x 6	250 x 150	526989	
12 x 4	300 x 100	526992	
12 x 6	300 x 150	526993	

	Dimension		Product Code
	inches	mm	

### 45° Wye Sp x Sp x Sp




			FOR USE WITH <b>MJ GREY™</b>
8	200	526987	
10 x 8	250 x 200	526990	
10	250	526991	
12 x 8	300 x 200	526994	
12 x 10	300 x 250	526995	
12	300	526996	

### Double 45° Wye H x H x H x H




1-1/2	40	526637
2	50	526456
2 x 1-1/2	50 x 40	526642
3	75	526639
3 x 1-1/2	75 x 40	526643
3 x 2	75 x 50	526644
4 x 3	100 x 75	526457
6	150	426752
8	200	426755
8 x 4	200 x 100	426753
8 x 6	200 x 150	526754
10	250	426759
10 x 4	250 x 100	426756
10 x 6	250 x 150	426757
10 x 8	250 x 200	426758
12	300	426764
12 x 4	300 x 100	426760
12 x 6	300 x 150	426761
12 x 8	300 x 200	426762
12 x 10	300 x 250	426763
14 x 4	350 x 100	526009
14 x 6	350 x 150	526005
16 x 4	400 x 100	526010
16 x 6	100 x 150	526772
18 x 4	450 x 100	526778
18 x 6	450 x 150	526779

### 45° Double Wye Sp x Sp x H x H



8 x 4	200 x 100	526769
8 x 6	200 x 150	526974
10 x 4	250 x 100	526976
10 x 6	250 x 150	526977
12 x 4	300 x 100	526980
12 x 6	300 x 150	526982

### 45° Double Wye Sp x Sp x Sp x Sp



			FOR USE WITH <b>MJ GREY™</b>
8	200	526975	
10	250	526979	
10 x 8	250 x 200	526978	
12 x 8	300 x 200	526983	
12 x 10	300 x 250	526984	