GOLD901[™]

Gold901™ is a lightweight, easy to install, 200 psi rated water service tubing that can be used on both the municipal and private-side of a project.

Gold901 is manufactured to Copper Tube Size (CTS) from High-Density Polyethylene (HDPE) and is third-party certified and listed to AWWA C901, CSA B137.1, NQ 3660-950 and NSF 61.

Gold901 is conveniently available in both coils and reels and is available in 3/4" to 2".

APPLICATIONS

Water Service Tubing

STANDARDS







ADVANTAGES

Non-corroding

Resistant to corrosive soils, aggressive water, stray electrical currents and moist environments

2) Lightweight

A 200 foot coil of 3/4" Gold901 weighs 20 lbs

3 Sequential Markings

Every 2 or 5 feet

Superior Flow

Hazen Williams C-Factor = 150

5) High Pressure

Rated at 200 psi at 73°F (1380 kPa at 23°C)

DIMENSIONS - GOLD901 TUBING

Nominal Size		Coil Length	Product	O.D.	I.D.	Min. Bend
in	mm	feet	Code	Avg (in)	Avg. (in)	Radius (in)
3/4	20	100	121402	0.875	0.671	19
		200 400	121403 121404			
		500	121404			
		3000	121406			
1	25	100	121407	1.125	0.863	23
		150	121408			
		200	121409			
		300	121410			
		500	121411			
		1000	121412			
		1500	121413			
1-1/4	32	100 300	121414 121415	1.375	1.055	30
1-1/2	40	100	121415	1.625	1.245	34
		250	121417			
		400	121418			
		1000	121419			
2	50	100	121420	2.125	1.629	44
		200	121421			
		500	121422			

Note: Custom coil and reel sizes may be available upon request.