

# GENERAL PLUMBING

## IPEX 04 GENERAL PURPOSE PVC CEMENT



CLEAR/GREY

Low VOC, 3 Year Shelf Life

Meets ASTM D2564. NSF and IAPMO listed for potable water and sewer pipe.

**Medium-bodied**, fast setting, PVC cement For rigid pipe sizes with interference fit through 160 mm (6") diameter. Sch 80 through 110 mm (4") diameter. For irrigation or drain. No primer needed for drainage applications unless required by local code.

ml	U.S.	Product Code Clear	Product Code Grey	Units per Case
118	1/4 pint	074314	–	24
236	1/2 pint	074313	–	24
473	pint	074312	–	12
946	quart	074311	–	12
3785	gallon	074310	074800	6



## IPEX 5 WET/DRY PRIMER



AQUA BLUE

3 Year Shelf Life

Meets the requirements of ASTM F656 for use with PVC pipe and fittings. NSF listed for potable water and sewer pipe.

Very fast acting primer especially formulated for use with IPEX 25 Wet/Dry cement. Excellent primer for wet applications or when quick penetration of pipe and fitting surfaces is desired. Can also be used with any other PVC or CPVC cement.

ml	U.S.	Product Code	Units per Case
476	pint	074397	12
946	quart	074398	12

