## THERMOPLASTIC VALVES

## **Manual & Actuated Thermoplastic Valves**

IPEX offers one of the most comprehensive ranges of high quality, high performance thermoplastic valves and actuation products available today. With more than 50 years of design and manufacturing experience, our lightweight, long life, maintenance free valves will save you time and money.

Material options such as PVC, CPVC, PP, PVDF, and ABS make our corrosion resistant valves ideal for use in a wide variety of applications. Quarter turn pneumatic and electric actuation, pneumatically actuated diaphragm valves, and many options and accessories allow for fully automated control. Whether a valve is required for isolation, diversion, control, or throttling, IPEX has a solution to meet your needs.

## **APPLICATIONS**

• Acid products handling for refineries, metal works, etc.

• Alum and ferric chloride handling

• Aquariums and aquatic animal life support systems

• Bleach, dye and acid lines

• Brine and seawater systems

• Chlorine injection, chlorine dioxide and chloralkali plant piping

Pharmaceutical

• Plant chemical distribution lines

• Plant water supply and distribution

· Swimming pools

Wash water recovery systems

Water and wastewater treatment



WHAT TYPE OF VALVE TO USE	Ball Valves	Butterfly Valves	Diaphragm Valves	Check & Vent Valves	Specialty Valves
On/Off Service	<b>✓</b>	✓			
High Capacity	<b>√</b>	✓			
Throttling	1	<b>✓</b>	<b>✓</b>		<b>✓</b>
Quick & Frequent Cycling	<b>√</b>				✓
Slurries/Dirty Fluids		<b>✓</b>	<b>✓</b>		
Filtering					✓
Back Flow Prevention				✓	
Air & Gas Release				✓	
Electro-Mechanical Control					✓
Actuation	✓	✓	✓		
			•		



## DV SERIES DIAPHRAGM VALVES - MANUAL HANDWHEEL

The DV is a rugged industrial product ideal for throttling or use in abrasive slurry lines. The raising position indicator also functions as an adjustable travel stop. This feature can be used to avoid over-compression of the EPDM or PTFE diaphragm, or as a travel limiter allowing different settings for the "closed" position. The molded flanged body eliminates potentially leaky joints while featuring end-to-end dimensions identical to most plastic lined metal diaphragm valves, allowing for direct replacement.

Pressure: up to 150 psi at 73°F depending on the size

Sizes: 1/2" - 6"

Size	Diaphragm	Flanged				
(in)	Material	Product Code	Universal #			
DV PVC BODY						
1/2	EPDM	052196	DVOV103			
	PTFE	052296	DVOV303			
3/4	EPDM	052197	DVOV104			
	PTFE	052297	DVOV304			
1	EPDM	052198	DVOV105			
	PTFE	052298	DVOV305			
1-1/2	EPDM	052207	DVOV107			
	PTFE	052299	DVOV307			
2	EPDM	052208	DVOV108			
	PTFE	052354	DVOV308			
3	EPDM	052209	DVOV109			
	PTFE	052355	DVOV309			
4	EPDM	052217	DVOV110			
	PTFE	052356	DVOV310			
6	EPDM	052218	DVOV111			
	PTFE	052357	DVOV311			

