



ACTIVE TELECOMMUNICATIONS ENCLOSURES

Enclosures install flush with the drop ceiling. Fully hinged, drop-down doors open to face the technician. Active enclosures are AC power ready and include a 9 CFM filtered fan capable of providing 100 air changes per hour. UL listed and plenum-rated.

2' X 2' ACTIVE CEILING ENCLOSURE accommodates one removable assembly with 2RU for active electronics and up to 5RU for 19" rack-mount patch panels and wire management.

2' X 4' ACTIVE CEILING ENCLOSURE includes two removable rack-mount assemblies with 4RU (total 8RU) for active components and up to 10RU for 19" rack-mount patch panels and wire management.

PASSIVE TELECOMMUNICATIONS ENCLOSURES

Three easy-to-install enclosures provide flexible consolidation point placement in the floor or ceiling. Manufactured of aluminum, enclosures are plenum rated and include fire-rated foam sealing kits.

2' X 2' PASSIVE FLOOR ENCLOSURES are ideal for use in air handling spaces under 8" deep raised floors, and hold two 4RU (8RU total) racks for standard 19" rack-mountable patch panels or wire management. UL listed.

2' X 2' PASSIVE CEILING ENCLOSURE accommodates up to 5RU of 19" rack-mountable patch panels and/or wire management.

WIRELESS ACCESS POINT ENCLOSURES

Enclosures are designed to house a variety of wireless access points. Wireless Ceiling Enclosures are plenum rated and mount into standard 2' x 2' ceiling tiles. Doors are fully hinged and lockable. UL listed.

10" and 5" DEEP CEILING ENCLOSURE accommodates one wireless access point. Door faceplates are sold separately to accommodate a variety of wireless equipment including Leviton's Enterprise Wireless Access Point (AP200).

4" DEEP CEILING ENCLOSURE accommodates one wireless access point or bridge. The removable door mounted bracket supports equipment up to 10-1/2" wide by 5-1/2" deep and 1-7/8" high.

WALL-MOUNT ENCLOSURES are constructed of rugged steel and include a lock assembly for areas with limited floor or ceiling space and a need for security. Inside space accommodates wireless equipment sized 9-1/2" wide by 6-1/2" high by 2-3/4" deep.

ACTIVE TELECOMMUNICATIONS ENCLOSURES	
Active Ceiling Enclosure, 2' x 2'	Z1000-AC2
Active Ceiling Enclosure, 2' x 4'	Z1000-AC4
PASSIVE TELECOMMUNICATIONS ENCLOSURES	
Passive Ceiling Enclosure, 2' x 2'	Z1000-PC2
Passive Raised-Floor Enclosure, 8" depth	Z1000-PF2
TELECOMMUNICATIONS ENCLOSURE ACCESSORIES	
Foam Kit for Zone Ceiling Enclosures	Z1000-FM1
Replacement Keys (2)	Z1000-KEY
Chrome Lock Kit	Z1000-LOK
WIRELESS ACCESS POINT ENCLOSURES	
Wireless Access Point Ceiling Enclosure, 10" Depth, w/o Faceplate	W1000-WCE
Wireless Access Point Ceiling Enclosure, 5" Depth, w/o Faceplate	W1000-WC5
Wireless Access Point Ceiling Enclosure, 4" Depth	W1000-WC0
Blank Faceplate (Fits 5" and 10" Wireless Access Point Enclosures)	W1000-F01
Faceplate for Cisco Aironet™ 350 (Fits 5" and 10" Wireless Access Point Enclosures)	W1000-F02
Faceplate for Cisco Aironet 1100 (Fits 5" and 10" Wireless Access Point Enclosures)	W1000-F03
Faceplate for Cisco Aironet 1200 (Fits 5" and 10" Wireless Access Point Enclosures)	W1000-F04
Faceplate for Leviton AP200 Wireless Access Point w/mounting bracket	W1000-F05
Wireless Access Point Wall-Mount Enclosure (Accommodates Cisco Aironet 350 or equivalent)	W1000-WW0