

COMBINATION DEVICES

MATERIAL CHARACTERISTICS

Decora Combination Switches

Environmental: Flammability UL-94, V2 Rating

Operating Temperature: -40°F to 248°F (-40°C to 120°C)

Switch/SmartLockPRO GFCI receptacle

Environmental: Flammability UL-94 V2 Rating

Operating Temperature: -31°F to 149°F (-35°C to 65°C)

TRADITIONAL

Leviton's Combination Devices offer pleasing, practical designs that fit standard wallboxes. Switch/switch, switch/receptacle and switch/pilot light combinations are available. These devices come in a range of colors and are backed by a limited two-year warranty.

Combination Devices



Description	Cat. No.	Rating	Color
15A			
Two Single Pole Switches, non-grounded	5224	15A-120/277VAC	W, I
Two Single Pole Switches with ground screw	5224-2	15A-120/277VAC	W, I, A, T
Single Pole Switch/Receptacle with ground screw	5225	Switch: 15A-120VAC Receptacle: 15A-125V	W, I, A, T
3-Way Switch/Receptacle with ground screw	5245	Switch: 15A-120VAC Receptacle: 15A-125V	W, I
3-Way Switch/Single Pole Switch with ground screw	5241	15A-120/277VAC	W, I, A, T
Two 3-Way Switches with ground screw	5243	15A-120/277VAC	W, I, A, T
Single Pole Switch/Pilot Light with ground screw	5226	Switch: 15A-120VAC Pilot Light: 1/25W-125VAC	W, I, A, T
3-Way Switch/Pilot Light with ground screw	5246	Switch: 15A-120VAC Pilot Light: 1/25W-125VAC	W, I, T
20A			
Two Single Pole Switches with ground screw	5334	20A-120/277VAC	W, I
Single Pole Switch/Receptacle with ground screw	5335	Switch: 20A-120VAC Receptacle: 20A-125V	W, I, E
Single Pole Switch/Pilot Light with ground screw	5336	Switch: 20A-120VAC Pilot Light: 1/25W-125VAC	I

COLOR

Basic Cat. Nos. shown above denotes Mahogany (Brown) color. To order colors, add suffix to basic Cat. No. White (-W), Ivory (-I), Almond (-A), Light Almond (-T), Ebony (-E).



5224-W



5225-W



5226-W