

57000 Series Panel Mount Devices

Specifications and Features

- For installation at main distribution panels.
- Hybrid suppression circuitry with built-in redundancy provides complete protection on all phases
- Modular design allows easy replacement of modules
- Provides Normal Mode (phase to neutral) and Common Mode (neutral to ground) protection for WYE configured 3-phase AC systems
- Disconnect options offer L-G path (7 mode)
- Dry contacts for remote monitoring allows use of the optional Remote Supervisor (Cat. No. 52000-RS)
- “Series connection” parallel operated (Kelvin/feed-through) rated for 100 Amps maximum continuous line current using #3 AWG conductors
- Dual-stage fuse protection for primary & secondary surge suppression circuits.
- Housed in NEMA-12 enclosure with hinged cover, surface or flush mountable.
- Limited Lifetime Product Warranty

57000 SERIES PANEL MOUNT DEVICES

Description	Cat. No. w/o Surge Counter	Cat. No. w/Surge Counter	Voltage Rating	Module
3-Phase WYE, 4-Wire & Ground	57120-M3	57120-CM3	120/208V AC	(3) 120 (1) 8120-GN
3-Phase WYE, 7-Mode, Integral Disconnect, 4-Wire & Ground	57120-M3S	57120-C3S	120/208V AC	(3) 120-M3S (1) 8120-GN
3-Phase Delta, 3-Wire & Ground	57240-DM3	—	240V AC	(3) 7240
3-Phase WYE, 4-Wire & Ground	57277-M3	57277-CM3	277/480V AC	(3) 7277 (1) 8320-GN
3-Phase WYE, 7-Mode, Integral Disconnect, 4-Wire & Ground	57277-M3S	57277-C3S	277/480V AC	(3) 7277-M3S (1) 8320-GN
3-Phase WYE, 4-Wire & Ground	57346-M3	—	346/600V AC	(3) 7346 (1) 8385-GN
3-Phase Delta, 3-Wire & Ground	57480-DM3	—	480V AC	(3) 7480
3-Phase Delta, 3-Wire & Ground	57600-DM3	—	600V AC	(3) 7600

