



## FEATURED PRODUCTS

Enclosures **B34**

Adapter Plates **B37**

Splice Trays & Holders **B39**

Splice Sleeves & Enclosure Accessories **B40**

## LightSpace® Enclosure System

Leviton offers a wide range of enclosures designed to protect, manage, and organize fiber splices across various indoor and outdoor environments. Specifically designed to meet the requirements of service providers large and small, LightSpace enclosures are ideal for central-office, outside-plant, and fiber-to-the-premises applications.



**KEY FEATURES**

- Large cable management rings for enhanced jumper routing
- Front cable management saddles
- Side entry for backbone cable
- Constructed of high-strength aluminum, powder-coated central-office white
- Mounts on standard 19" and 23" racks and cabinets
- Accepts LightSpace adapter plates (see pages B37-B38)



**RECOMMENDED APPLICATIONS:**

Central Office or Head End, CLEC  
19" and 23" Racks and Cabinets

**DP SERIES OPTICAL DISTRIBUTION ENCLOSURES**

- Removable front door
- Rear door with key lock option
- Upper and lower patch cord bend radius brackets

For assistance customizing your enclosures, please visit [Leviton.com/configurator](http://Leviton.com/configurator) or call Tech Support at 800.824.3005.

**DPS & DPC SERIES OPTICAL SPLICE ENCLOSURES**

- Front accessibility to splice trays
- Removable front door with key lock option
- Rear door with key lock option
- Connector identification label

**LIGHTSPACE DP OPTICAL DISTRIBUTION ENCLOSURES, STANDARD PART NUMBERS**

DESCRIPTION	MAXIMUM CAPACITY			PART NO.
	FIBERS (USING LC)	ADAPTER PLATES	AND SPLICE TRAYS*	
DP-525, 3RU, empty^	144	6	N/A	DP03U-STD
<b>[A]</b> DP-700, 4RU, empty^	288	12	N/A	DP04U-STD
DP-105, 6RU, empty°	288	12	N/A	DP06U-STD

**LIGHTSPACE DPS OPTICAL SPLICE ENCLOSURES, STANDARD PART NUMBERS**

DPS-525, 3RU, empty	N/A	N/A	4	DPS3U-STD
<b>[B]</b> DPS-700, 4RU, empty	N/A	N/A	6	DPS4U-STD
DPS-105, 6RU, empty	N/A	N/A	12	DPS6U-STD

**LIGHTSPACE DPC OPTICAL DISTRIBUTION & SPLICE ENCLOSURES, STANDARD PART NUMBERS**

DPC-525, 6RU, empty^	144	6	4	DPC6U-033
<b>[C]</b> DPC-700, 8RU, empty^	288	12	6	DPC8U-STD
DPC-105, 12RU, empty°	288	12	12	DPC12-066

\* = Maximum splice tray capacity is limited by height of selected splice tray. See page X1.3 for splice tray dimension and selection guide.  
^ = Accepts LightSpace (LGX® footprint) 6- or 8-pack adapter plates.  
° = Accepts LightSpace 12-pack adapter plates.