

## 30A, 50A and 60A Devices

### Industrial Grade Power Devices

Built from durable thermoplastic, Leviton power receptacles — in flush mount, surface mount and panel mount versions — come equipped with heavy-gauge, double-wire copper alloy contacts. To ensure correct and speedy wiring, terminals have ID markings. Flush mount receptacles fit Leviton's wide range of 2.15"-diameter wallplates and mounting hardware is included. Angle plugs are made of tough, heavy-duty nylon for a long dependable service life.

#### 279-PM, 5054 and 279



#### Features and Benefits

- Heavy-gauge, double-wipe copper alloy contacts
- Easy-to-wire terminals accept up to #4 AWG conductors
- Terminals marked for easy identification and fast wiring
- All mounting hardware included
- Flush-mount devices fit single or two-gang outlet boxes
- Surface-mount devices are commercial grade and have concentric knockouts for 3/4" and 1" conduit and adjustable cord clamp for back and bottom entrance of cable

#### Angle Plugs

- Rugged cord clamp for secure cable grip accommodates cord diameters from .625" to 1.375" and does not tear conductor jacket
- Made of tough, heavy-duty nylon for long service life
- Devices feature heavy-sectioned dead-front right-angle
- Pressure-clamp terminal design
- Terminals accept up to #4 AWG stranded conductors
- Four-way positioning front module
- Solid brass blades for maximum conductivity

**30A, 50A, 60A | Power Devices**

**30A, 50A and 60A Industrial Grade Power Devices**

**3-Pole, 4-Wire, Grounding**

<b>Rating</b>	<b>30A-125/250V</b>		
NEMA			
	14-30P	14-30R	
<b>Description</b>	<b>Cat. No.</b>	<b>Cat. No.</b>	<b>Wallplate Information</b>
Flush Mount Receptacle	—	278	Fits all wallplates with 2.15" diameter center hole
Panel Mount Receptacle	—	278-PM	Fits all wallplates with 2.15" diameter center hole
Surface Mount Receptacle	—	55054	Fits all wallplates with 2.15" diameter center hole
Angle Plug	9432-P	—	



279-PM

<b>Rating</b>	<b>50A-125/250V</b>		
NEMA			
	14-50P	14-50R	
<b>Description</b>	<b>Cat. No.</b>	<b>Cat. No.</b>	<b>Wallplate Information</b>
Flush Mount Receptacle	—	279	Fits all wallplates with 2.15" diameter center hole
Panel Mount Receptacle	—	279-PM	Fits all wallplates with 2.15" diameter center hole
Surface Mount Receptacle	—	55050	Fits all wallplates with 2.15" diameter center hole
Angle Plug	9452-P	—	



55050

<b>Rating</b>	<b>60A-125/250V</b>		
NEMA			
	14-60P	14-60R	
<b>Description</b>	<b>Cat. No.</b>	<b>Cat. No.</b>	<b>Wallplate Information</b>
Flush Mount Receptacle	—	9460	Fits all wallplates with 2.465" diameter center hole
Flush Mount Receptacle, Isolated Ground	—	9460-IG	Fits all wallplates with 2.465" diameter center hole
Angle Plug	9462-P	—	



9460

**3-Pole, 4-Wire, 3 Phase, Grounding**

<b>Rating</b>	<b>30A-250V 3Ø</b>		
NEMA			
	15-30P	15-30R	
<b>Description</b>	<b>Cat. No.</b>	<b>Cat. No.</b>	<b>Wallplate Information</b>
Flush Mount Receptacle	—	8430	Fits all wallplates with 2.465" diameter center hole
Angle Plug	8432-P	—	



8430

<b>Rating</b>	<b>50A-250V 3Ø</b>		
NEMA			
	15-50P	15-50R	
<b>Description</b>	<b>Cat. No.</b>	<b>Cat. No.</b>	<b>Wallplate Information</b>
Flush Mount Receptacle	—	8450	Fits all wallplates with 2.465" diameter center hole
Flush Mount Receptacle, Isolated Ground	—	8450-IG	Fits all wallplates with 2.465" diameter center hole
Angle Plug	8452-P	—	



8452-P

Continued on next page