

Decora® Combination Devices

Decora® combination devices offer switch/switch, switch/receptacle and switch/pilot light pairings in sleek packages suitable for the finest interiors. For the ultimate in convenience and safety, the Decora® Combination Switch/SmartlockPro® GFCI receptacles pair a single pole switch with a GFCI receptacle equipped with Leviton's pioneering true dead-face design. The USB Charger Devices offers powerful charging capabilities to get your electronic devices up and running fast.

Sample Decora® Combination Devices



Features and Benefits

- Elegant Decora® styling provides multiple controls in a single-gang wallbox
- Impact-resistant thermoplastic and double-wipe contacts
- Common shunted internally to all switches
- Limited 2-year warranty

Tamper-Resistant Receptacles

- Shutter mechanism inside the receptacle blocks access to the contacts unless a two-prong plug is inserted, helping ensure hairpins, keys, etc., will be locked out
- TR symbol on residential receptacles assures they meet the 2008 NEC requirement
- Heavy-duty construction offers long, trouble-free service life

USB Charger Devices

- Smart chip recognizes and optimizes the charging requirements of the connected device
- Compatible with most tablets and other electronic mobile devices
- Vertical ports for easy maneuvering and reduced stress on USB cables

Hospital Grade USB Charger (Added Features)

- Self-grounding clip
- Extra heavy-duty impact-resistant polyester cover

All SmartlockPro® GFCI Combination Devices

- TEST/RESET buttons match device color
- Dual function LED indicator light — provides indication of wiring error and power availability

SmartlockPro® GFCI/Sensor Guide Light

- Manual control of sensor light using the TEST/RESET buttons
- Long-lasting, energy efficient LEDs with 20-year life expectancy — no bulbs to replace
- Light sensor provides automatic ON/OFF features

SmartlockPro® GFCI/Switch

- Replaces standard switch/outlet combination devices in residential and light commercial installations
- Permits multiple wiring options that allow for GFCI protection of switched load and downstream receptacles

Color Choices Decora® combination devices are offered in a wide range of colors. To order colors, add suffix to Cat. No.



White (-W)



Ivory (-I)



Light Almond (-T)



Gray (-G/-GY)



Black (-E)



Brown



Red (-R)

Combination Devices

RESIDENTIAL



DECORA® | 15A, 20A

Continued from previous page

15A, 20A Combination Switches*

Rating	Switch: 15A-120VAC Pilot Light: 1/25W-125VAC		
Description	Color	Cat. No.	
3-Way Switch/ Receptacle	White	5645-W	
	Ivory	5645-I	
	Black	5645-E	

Rating	Individual Switches: 15A-120V Device Total: 20A-120V		Individual Switches: 15A-120V Device Total: 20A-120V	
Description	Color	Cat. No. Non-grounded	Cat. No. with Ground Screw	
Dual Rockers	White	1754-W	1754-2W	
	Ivory	1754-I	—	
	Light Almond	1754-T	—	
Illuminated Dual Rockers (Light is ON when top rocker is OFF)	White	1754-ILW	—	
	Ivory	1754-ILI	—	
Three Rockers	White	1755-W	1755-2W	
	Ivory	1755-I	1755-2I	
	Light Almond	1755-T	—	



1755-W

*Warning: Although each individual rocker switch is rated up to 15A-120V, the total combined load for both duplex or all three triplex switches must not exceed 20 Amps

Decora® USB Charger Combination Devices

15A, 20A USB Charger Combination Switches

Rating	USB Port: 3.6A Receptacle: 15A-125V		USB Port: 3.6A Receptacle: 20A-125V	
Description	Color	Cat. No.	Cat. No.	
USB Charger/ Tamper-Resistant Receptacle	White	T5631-2W	—	
	Light Almond	T5631-T	—	
	Black	T5631-E	—	
USB Charger/Duplex Tamper-Resistant Receptacle	White	T5632-W	T5832-W	
	Ivory	T5632-I	T5832-I	
	Light Almond	T5632-T	T5832-T	
	Black	T5632-E	T5832-E	
	Gray	T5632-GY	T5832-GY	
	Brown	T5632-B	—	
	Hospital Grade	White	T5632-HGW	T5832-HGW
USB Charger/Duplex Tamper-Resistant Receptacle	Ivory	T5632-HGI	T5832-HGI	
	Light Almond	T5632-HGT	T5832-HGT	
	Black	T5632-HGE	T5832-HGE	
	Gray	T5632-HGG	T5832-HGG	
	Brown	T5632-HG	T5832-HG	
	Red	T5632-HGR	T5832-HGR	

Rating	USB Port: 4.2A	
Description	Color	Cat. No.
4-Port USB Charger	White	USB4P-W
	Ivory	USB4P-I
	Light Almond	USB4P-T
	Black	USB4P-E
	Gray	USB4P-GY



T5632-HGW



T5832-W



USB4P-W