

## 15A | Watertight

# Wetguard® Watertight Locking Plugs, Connectors, Inlets, Outlets and Receptacles

### Features and Benefits

- Corrosion-resistant electroless nickel-coated brass blades, contacts, terminal screws and wiring clamps, and stainless steel assembly screws make these devices ideal for use in wet and corrosive environments
- EPTR rubber part provides outstanding resistance to wet and damp environments, extreme temperature variations, water, acids, alkalis, grease, oils and many automotive and industrial lubricants and solvents
- Plug and connector husk is molded to a bondable nylon body, providing a device that withstands physical abuse
- Interlocking “tongue and groove” construction seals out water, moisture and dirt when plugs are mated with connectors
- Multi-point sealing system utilizes nut, strain relief washer and rubber bushing to form a watertight cord grip seal
- Non-magnetic stainless steel fast-threading assembly screws won't interfere with sensitive equipment
- Connector “hood” closure cap seals device when not in use
- Most devices also available in black. Check for availability
- Devices are UL and CSA listed and have enclosure ratings of NEMA 4, 4X, 12 and IEC IP66, IP67 when mated or with cover closed
- Backed by a lifetime warranty

## Wetguard® Locking Plugs, Connectors, Inlets, Outlets and Receptacles

### 15A Wetguard® Locking Devices

Rating	15A-125V	15A-125V	15A-250V	15A-277V	
Configuration	2P 2W	2P 3W	2P 3W	2P 3W	
NEMA	L1-15	L5-15	L6-15	L7-15	
Description	Color	Cat. No.	Cat. No.	Cat. No.	Cat. No.
Plug	Yellow	24W04	24W47*	24W49	24W34
Plug Cap		14W*	14W*	14W*	14W*
Connector		25W04	25W47*	25W49	25W34
Connector Cap		50W50*	50W50*	50W50*	50W50*
Single Outlet		95W04-S	95W47-S	95W49-S	95W34-S
Duplex Outlet		85W04-D	85W47-D	85W49-D	85W34-D
Single Inlet		64W04	64W47	64W49	64W34
Connector for Single Inlet		74W04-C	74W47-C	74W49-C	74W34-C
Single Receptacle		—	47CM-10	45CM-60	47CM-60
Receptacle Cover w/Gasket		—	60W03*	60W03*	60W03*



24W04



50W50

NEMA configuration diagrams represent plug blade configuration.  
 \*Available in black. To order, add “-B” suffix to catalog number

### SPOTLIGHT

#### Wetguard® Watertight Wiring Devices

The Wetguard® line consists of a comprehensive array of plugs, connectors, inlets, outlets, covers and an industry exclusive FD Box system that allows mounting of single-gang devices in multi-gang configurations. Visit [www.leviton.com/wetguard](http://www.leviton.com/wetguard) for more information.



## 20A AND 20/10A | Watertight

Continued from previous page

### Wetguard® Locking Plugs, Connectors, Inlets, Outlets and Receptacles

#### 20A and 20/10A Wetguard® Locking Devices

Rating		20A-125/250V	20A-3Ø 250V	20A-3Ø 480V	20A-3ØY 120/208V	
Configuration		3P 4W	3P 4W	3P 4W	4P 4W	
NEMA		 L14-20	 L15-20	 L16-20	 Non-NEMA	
Description	Color	Cat. No.	Cat. No.	Cat. No.	Cat. No.	
Plug	Yellow	26W74	26W75*	26W76*	26W09	
Plug Cap		26W*	26W*	26W*	26W*	
Connector		27W74	27W75*	27W76*	27W09	
Connector Cap		50W52*	50W52*	50W52*	50W52*	
Single Outlet		97W74-S	97W75-S	97W76-S	97W09-S	
Duplex Outlet		—	—	—	—	
Single Inlet		66W74	66W75	66W76	66W09	
Connector for Single Inlet		76W74-C	76W75-C	76W76-C	76W09-C	
Single Receptacle		24CM-10	24CM-20	24CM-30	7410-B	
Receptacle Cover w/Gasket		60W04*	60W04*	60W04*	60W04*	
Rating			20A-3ØY 120/208V	20A-3ØY 277/480V	20A-3ØY 347/600V	20A-250V 10A-600V
Configuration			4P 5W	4P 5W	4P 5W	4P 5W
NEMA			 L21-20	 L22-20	 L23-20	 Non-NEMA
Description	Color	Cat. No.	Cat. No.	Cat. No.	Cat. No.	
Plug	Yellow	26W81*	26W82	26W83	26W10	
Plug Cap		26W*	26W*	26W*	26W*	
Connector		27W81*	27W82	27W83	27W10	
Connector Cap		50W52*	50W52*	50W52*	50W52*	
Single Outlet		97W81-S	97W82-S	97W83-S	97W10-S	
Duplex Outlet		—	—	—	—	
Single Inlet		66W81	66W82	66W83	66W10	
Connector for Single Inlet		76W81-C	76W82-C	76W83-C	76W10-C	
Single Receptacle		2510	2520	2530	—	
Receptacle Cover w/Gasket		60W04*	60W04*	60W04*	60W04*	

NEMA configuration diagrams represent plug blade configuration.  
\*Available in black. To order, add "-B" suffix to catalog number



26W74



66W76



26W



27W81



#### Related Products

See section H for more information on the entire line of watertight wiring devices.

30A Wetguard® Locking Devices					
<b>Rating</b>		30A-125V	30A-250V	30A-277V	30A-125/250V
<b>Configuration</b>		2P 3W	2P 3W	2P 3W	3P 3W
NEMA					
		L5-30	L6-30	L7-30	Non-NEMA
Description	Color	Cat. No.	Cat. No.	Cat. No.	Cat. No.
Plug	Yellow	28W47*	28W48*	28W49	28W08
Plug Cap		28W*	28W*	28W*	28W*
Connector		29W47*	29W48*	29W49	29W08
Connector Cap		50W54*	50W54*	50W54*	50W54*
Single Outlet		99W47-S	99W48-S	99W49-S	99W08-S
Single Inlet		68W47	68W48	68W49	68W08
Connector for Single Inlet		78W47-C	78W48-C	78W49-C	78W08-C
Single Receptacle		26CM-10	26CM-20	2630	3330
Receptacle Cover w/Gasket		60W05*	60W05*	60W05*	60W05*
<b>Rating</b>		30A-125/250V	30A-3Ø 250V	30A-3Ø 480V	30A-3ØY 600V
<b>Configuration</b>		3P 4W	3P 4W	3P 4W	3P 4W
NEMA					
		L14-30	L15-30	L16-30	L17-30
Description	Color	Cat. No.	Cat. No.	Cat. No.	Cat. No.
Plug	Yellow	28W74	28W75	29W76*	28W77
Plug Cap		28W*	28W*	28W*	28W*
Connector		29W74	29W75	29W76*	29W77
Connector Cap		50W54*	50W54*	50W54*	50W54*
Single Outlet		99W74-S	99W75-S	99W76-S	99W77-S
Single Inlet		68W74	68W75	68W76	68W77
Connector for Single Inlet		78W74-C	78W75-C	78W76-C	78W77-C
Single Receptacle		27CM-10	27CM-20	2730	2740
Receptacle Cover w/Gasket		60W05*	60W05*	60W05*	60W05*
<b>Rating</b>		30A-3ØY 120/208V	30A-3ØY 120/208V	30A-3ØY 277/480V	30A-3ØY 347/600V
<b>Configuration</b>		4P 4W	4P 5W	4P 5W	4P 5W
NEMA					
		Non-NEMA	L21-30	L22-30	L23-30
Description	Color	Cat. No.	Cat. No.	Cat. No.	Cat. No.
Plug	Yellow	28W09	28W81	28W82	28W83
Plug Cap		28W*	28W*	28W*	28W*
Connector		29W09	29W81	29W82	29W83
Connector Cap		50W54*	50W54*	50W54*	50W54*
Single Outlet		99W09-S	99W81-S	99W82-S	99W83-S
Single Inlet		68W09	68W81	68W82	68W83
Connector for Single Inlet		78W09-C	78W81-C	78W82-C	78W83-C
Single Receptacle		3430	2810	2820	2830
Receptacle Cover w/Gasket		60W05*	60W05*	60W05*	60W05*



28W47



29W48



99W76



50W54

NEMA configuration diagrams represent plug blade configuration.  
 \*Available in black. To order, add "B" suffix to catalog number