

| 15/10A and 20A Wetguard® Locking Devices |                      |          |          |
|--|----------------------|----------|----------|
| Rating                                   | 15A-125V<br>10A-250V |          | 15A-125V |
| Configuration                            | 3P 2W                |          | 2P 3W    |
| NEMA                                     | Non-NEMA             |          | L5-15    |
| Description                              | Color                | Cat. No. | Cat. No. |
| Plug                                     | Yellow               | 24W07    | 26W07    |
| Plug Cap                                 |                      | 14W*     | 14W*     |
| Connector                                |                      | 25W07    | 27W07    |
| Connector Cap                            |                      | 50W50*   | 50W50*   |
| Single Outlet                            |                      | 95W07-S  | 97W07-S  |
| Duplex Outlet                            |                      | 85W07-D  | 87W07-D  |
| Single Inlet                             |                      | 64W07    | 66W07    |
| Connector for Single Inlet               |                      | 74W07-C  | 76W07-C  |
| Single Receptacle                        |                      | —        | —        |
| Receptacle Cover w/Gasket                |                      | —        | —        |



24W07



85W07-D

| 20A and 20/10A Wetguard® Locking Devices |          |          |          |          |          |              |                      |
|--|----------|----------|----------|----------|----------|--------------|----------------------|
| Rating                                   | 20A-125V |          | 20A-250V | 20A-277V | 20A-347V | 20A-125/250V | 20A-250V<br>10A-600V |
| Configuration                            | 2P 3W    |          | 2P 3W    | 2P 3W    | 2P 3W    | 3P 3W        | 3P 3W                |
| NEMA                                     | L5-20    |          | L6-20    | L7-20    | L24-20   | Non-NEMA     | Non-NEMA             |
| Description                              | Color    | Cat. No. | Cat. No. | Cat. No. | Cat. No. | Cat. No.     | Cat. No.             |
| Plug                                     | Yellow   | 26W47*   | 26W48*   | 26W49    | 22W07    | 26W08        | 26W08-G              |
| Plug Cap                                 |          | 26W*     | 26W*     | 26W*     | 26W*     | 26W*         | 26W*                 |
| Connector                                |          | 27W47*   | 27W48*   | 27W49    | 23W07    | 27W08        | 27W08-G              |
| Connector Cap                            |          | 50W52*   | 50W52*   | 50W52*   | 50W52*   | 50W52*       | 50W52*               |
| Single Outlet                            |          | 97W47-S  | 97W48-S  | 97W49-S  | 93W07-S  | 97W08-S      | —                    |
| Duplex Outlet                            |          | —        | —        | —        | —        | —            | —                    |
| Single Inlet                             |          | 66W47    | 66W48    | 66W49    | 68W29    | 66W08        | —                    |
| Connector for Single Inlet               |          | 76W47-C  | 76W48-C  | 76W49-C  | 78W29-C  | 76W08-C      | —                    |
| Single Receptacle                        |          | 23CM-10  | 23CM-20  | 23CM-30  | —        | 7310-B       | —                    |
| Receptacle Cover w/Gasket                |          | 60W04*   | 60W04*   | 60W04*   | —        | 60W04*       | —                    |



26W47



27W47

NEMA configuration diagrams represent plug blade configuration.  
\*Available in black. To order, add “-B” suffix to catalog number

Continued on next page



### Related Products

See section H for more information on the entire line of watertight wiring devices.

## Locking Plugs, Connectors, Inlets, Outlets and Receptacles

### Product Overview

#### Features and Benefits

- Corrosion-resistant electroless nickel-coated brass blades, contacts, terminal screws and wiring clamps, and stainless steel assembly screws make these devices ideal for use in wet and corrosive environments
- EPTR rubber part provides outstanding resistance to wet and damp environments, extreme temperature variations, water, acids, alkalis, grease, oils and many automotive and industrial lubricants and solvents
- Plug and connector husk is molded to a bondable nylon body, providing a device that withstands physical abuse
- Interlocking “tongue and groove” construction seals out water, moisture and dirt when plugs are mated with connectors
- Multi-point sealing system utilizes nut, strain relief washer and rubber bushing to form a watertight cord grip seal
- Non-magnetic stainless steel fast-threading assembly screws won't interfere with sensitive equipment
- Connector “hood” closure cap seals device when not in use
- Most devices also available in black. Check for availability
- Devices are UL and CSA listed and have enclosure ratings of NEMA 4, 4X, 12 and IEC IP66, IP67 when mated or with cover closed
- Backed by a lifetime warranty

#### Wetguard® Watertight Locking Devices



Plug



Plug Cap



Connector



Connector Cap



Single Outlet



Duplex Outlet



Single Inlet



Connector Mates w/Inlet



Single Receptacle



Receptacle Cover

**WETGUARD® LOCKING DEVICES | 20A and 20/10A**
**Locking Devices — 20A and 20/10A**

| 20A and 20/10A Wetguard® Locking Devices |                |                    |          |          |           |               |               |               |              |                            |                   |                           |  |
|--|----------------|--------------------|----------|----------|-----------|---------------|---------------|---------------|--------------|----------------------------|-------------------|---------------------------|--|
|  |                |                    | Cat. No. |          |           |               |               |               |              |                            |                   |                           |  |
| Amp                                      | Volt           | NEMA Configuration | Plug     | Plug Cap | Connector | Connector Cap | Single Outlet | Duplex Outlet | Single Inlet | Connector for Single Inlet | Single Receptacle | Receptacle Cover w/Gasket |  |
| <b>2-Pole, 3-Wire</b>                    |                |                    |          |          |           |               |               |               |              |                            |                   |                           |  |
| 20                                       | 125            | L5-20              | 26W47*   | 26W*     | 27W47*    | 50W52*        | 97W47-S       | —             | 66W47        | 76W47-C                    | 23CM-10           | 60W04*                    |  |
| 20                                       | 250            | L6-20              | 26W48*   | 26W*     | 27W48*    | 50W52*        | 97W48-S       | —             | 66W48        | 76W48-C                    | 23CM-20           | 60W04*                    |  |
| 20                                       | 277            | L7-20              | 26W49    | 26W*     | 27W49     | 50W52*        | 97W49-S       | —             | 66W49        | 76W49-C                    | 23CM-30           | 60W04*                    |  |
| 20                                       | 347            | L24-20             | 22W07    | 26W*     | 23W07     | 50W52*        | 93W07-S       | —             | 68W29        | 78W29-C                    | —                 | —                         |  |
| <b>3-Pole, 3-Wire</b>                    |                |                    |          |          |           |               |               |               |              |                            |                   |                           |  |
| 20                                       | 125/<br>250    | Non-NEMA           | 26W08    | 26W*     | 27W08     | 50W52*        | 97W08-S       | —             | 66W08        | 76W08-C                    | 7310-B            | 60W04*                    |  |
| 20                                       | 250            | Non-NEMA           | 26W08-G  | 26W*     | 27W08-G   | 50W52*        | —             | —             | —            | —                          | —                 | —                         |  |
| 10                                       | 600            | Non-NEMA           |          |          |           |               |               |               |              |                            |                   |                           |  |
| <b>3-Pole, 4-Wire</b>                    |                |                    |          |          |           |               |               |               |              |                            |                   |                           |  |
| 20                                       | 125/<br>250    | L14-20             | 26W74    | 26W*     | 27W74     | 50W52*        | 97W74-S       | —             | 66W74        | 76W74-C                    | 24CM-10           | 60W04*                    |  |
| 20                                       | 3Ø 250         | L15-20             | 26W75*   | 26W*     | 27W75*    | 50W52*        | 97W75-S       | —             | 66W75        | 76W75-C                    | 24CM-20           | 60W04*                    |  |
| 20                                       | 3Ø 480         | L16-20             | 26W76*   | 26W*     | 27W76*    | 50W52*        | 97W76-S       | —             | 66W76        | 76W76-C                    | 24CM-30           | 60W04*                    |  |
| <b>4-Pole, 4-Wire</b>                    |                |                    |          |          |           |               |               |               |              |                            |                   |                           |  |
| 20                                       | 3ØY<br>120/208 | Non-NEMA           | 26W09    | 26W*     | 27W09     | 50W52*        | 97W09-S       | —             | 66W09        | 76W09-C                    | 7410-B            | 60W04*                    |  |
| <b>4-Pole, 5-Wire</b>                    |                |                    |          |          |           |               |               |               |              |                            |                   |                           |  |
| 20                                       | 3ØY<br>120/208 | L21-20             | 26W81*   | 26W*     | 27W81*    | 50W52*        | 97W81-S       | —             | 66W81        | 76W81-C                    | 2510              | 60W04*                    |  |
| 20                                       | 3ØY<br>277/480 | L22-20             | 26W82    | 26W*     | 27W82     | 50W52*        | 97W82-S       | —             | 66W82        | 76W82-C                    | 2520              | 60W04*                    |  |
| 20                                       | 3ØY<br>347/600 | L23-20             | 26W83    | 26W*     | 27W83     | 50W52*        | 97W83-S       | —             | 66W83        | 76W83-C                    | 2530              | 60W04*                    |  |
| 20                                       | 250            | Non-NEMA           | 26W10    | 26W*     | 27W10     | 50W52*        | 97W10-S       | —             | 66W10        | 76W10-C                    | —                 | 60W04*                    |  |
| 10                                       | 600            | Non-NEMA           |          |          |           |               |               |               |              |                            |                   |                           |  |

NEMA configuration diagrams represent plug blade configuration.  
 \*Available in black. To order, add “-B” suffix to catalog number