

**HID** | Mogul Base Incandescent

## High Intensity Discharge Mogul Base Incandescent Lampholders

### Features and Benefits

- Moguls listed have white glazed porcelain bodies except for 8750 (yellow), 8751 (pink), and 8746 (gray glazed with ceramic arc shield)
- Copper-alloy nickel-plated screw shell

### Porcelain Mogul Base Lampholders

#### With Leads

Description	Outer Diameter	Overall Height	Rating	Cat. No.
Keyless, Single Circuit. For high pressure sodium lamps up to 1000 watts. 8-32 mounting screws on 1 <sup>3</sup> / <sub>8</sub> " centers	2 1 <sup>1</sup> / <sub>8</sub> "	3 3 <sup>3</sup> / <sub>64</sub> "	1500W 600V 5KV Pulse rated	8746
Keyless, Single Circuit. Position-oriented. For Super Metalarc HID lamps. 8-32 mounting screws on 13/8" centers	2 5 <sup>5</sup> / <sub>32</sub> "	2 39 <sup>39</sup> / <sub>64</sub> "	1500W 600V Pulse rated	8750
Keyless, Single Circuit. For high-pressure sodium lamps up to 400 watts. 8-32 mounting screws on 1 <sup>3</sup> / <sub>8</sub> " centers	2 5 <sup>5</sup> / <sub>32</sub> "	2 39 <sup>39</sup> / <sub>64</sub> "	1500W 600V 4KV Pulse rated	8756
Low Pressure Sodium. For use with all single-end bayonet base low pressure sodium lamps*~	1 3 <sup>3</sup> / <sub>8</sub> "	1 5 <sup>5</sup> / <sub>8</sub> "	660W 1000V	8806
Designed for Open-Fixture Shielded Metal Halide Lamps. Complies with NFPA 70-2005 for open-rated fixtures. 8-32 mounting screws on 1 <sup>3</sup> / <sub>8</sub> " centers	2 5 <sup>5</sup> / <sub>32</sub> "	2 39 <sup>39</sup> / <sub>64</sub> "	1500W 600V 4KV Pulse Rated	8751

Leads types, lengths and ratings vary with the end use applications.  
Standard leads as well as variations available on inquiry.  
CSA Certified except where indicated by \* and NOM Certified except where indicated by ~

#### Screw Terminals

Description	Outer Diameter	Overall Height	Rating	Cat. No.
Keyless; 2-Piece; Single-Pole*	2 5 <sup>5</sup> / <sub>16</sub> "	2 23 <sup>23</sup> / <sub>64</sub> "	1500W 600V	8765
Keyless;. Single Circuit with 8-32 Lock Nuts on 1 <sup>3</sup> / <sub>8</sub> " Centers. Die-cast caps available upon request	2 5 <sup>5</sup> / <sub>32</sub> "	2 23 <sup>23</sup> / <sub>64</sub> "	1500W 600V	8694

CSA Certified except where indicated by \*



8746



8750



8806



8694

#### Related Products

Leviton offers a wide selection of occupancy and vacancy sensors for residential and commercial applications.  
**See pages N-2 to N-32 in the Energy Management section for more information.**

