

Ocal[®] hstallation Products

Protects, lubricates and enhances the conductivity of all electrical connections!

KOPR-SHIELD® Joint Compound

- Meets NEC[®] requirements for protection against corrosion: "Where corrosion protection is necessary and the conduit is threaded in the field, all threads shall be coated with an approved electrically conductive, corrosion-resistant compound."
- Extremely adhesive compound flows smoothly into uneven contours and voids, ensuring easy application and complete, positive protection and lubrication
- Won't settle out, thin, thicken, harden or dry out under the most severe environmental conditions
- Excellent temperature characteristics can be brushed on at -50° F to 250° F (-45° C to 121° C) and remains intact for short periods even at 1,800° F (982° C)
- · Ensures low resistance and seals out air and moisture
- Unique, homogenized blend of pure, polished colloidal copper, rust and corrosion inhibitors

NEC and National Electrical Code are registered trademarks of the National Fire Protection Association, Inc.



KOPR-SHIELD® Joint Compound

CAT. NO.	CONTAINER	SIZE	
201-31879	Brush Cap Can	11/2 oz. (.04 liter)	
201-31879-1	Brush Cap Can	4 oz. (.12 liter)	
CP8-TB	Brush Cap Can	8 oz. (.24 liter)	
CP16	Brush Cap Can	1 pint (.47 liter)	
CP128	Can	1 gallon (3.79 liter)	

Note: Not recommended for food & beverage processing applications.

Fast-drying, air-cure patch for Ocal[®] conduit and fittings.

Ocal® Touch-Up Compounds

CAT. NO.	CONTAINER	SIZE	COLOR	
Exterior PVC Patch				
SPRAY-G	Spray Can	121/2 oz. (.37 liter)	Dark Gray	
SPRAY-W	Spray Can	121/2 oz. (.37 liter)	White	
SPRAY-B	Spray Can	121/2 oz. (.37 liter)	Light Blue	
PATCHP-G	Brush Cap Can	1 pint (.47 liter)	Dark Gray	
PATCHP-W	Brush Cap Can	1 pint (.47 liter)	White	
PATCHP-B	Brush Cap Can	1 pint (.47 liter)	Light Blue	
PATCHG-G	Bottle	1 gallon (3.79 liter)	Dark Gray	
PATCHG-W	Bottle	1 gallon (3.79 liter)	White	
PATCHG-B	Bottle	1 gallon (3.79 liter)	Light Blue	
Interior Urethane Patch				
URETHANEPATCH	Brush Cap Can	1 pint (.47 liter)	Blue	



www.tnb.com

United States Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354 Technical Services Tel: 888.862.3289



(VL) (SP