

Molded Case Circuit Breakers

Molded Case Switch — Circuit Disconnect

Selection

Maximum Frame Amp Rating	2-Pole		3-Pole		Self-Protective Instantaneous Override $\pm 20\%$ ^③
	Catalog Number	List Price \$	Catalog Number	List Price \$	
100	BQ2S060■ BQ2S100■		BQ3S060■ BQ3S100■		1000 1000
125	ED22S100A■ ED42S100A■ ED42S125A■ ED62S100A■ — CED62S100A■ CED62S125A■		ED23S100A ED43S100A ED43S125A ED63S100A ED63S125A CED63S100A■ CED63S125A■		1000 1000 1000 1000 1000 1000 1000
225	QJ22S225A■		QJ23S225A		2000
250	FXD62S250A HFxD62S250A■ ①		FXD63S250A HFxD63S250A■ CFD63S250A■		3200 3200 3200
400	JXD22S400A■ — — ①	— — —	JXD23S400A JXD63S400A HJXD63S400A■ CJD63S400A■		6000 6000 6000 6000
600	— — ①	— — —	LXD63S600A HLXD63S600A■ CLD63S600A■		8000 8000 8000
800	— — ①	— — —	LMXD63S800A■ MXD63S800A CMD63S800A		10000 10000 10000
1200	— ①	— —	NXD63S120A CND63S120A■		10000 10000
1600	①	—	PXD63S160A ^④		10000
2000	①	—	RXD63S200A■ ^⑤		10000
Non Automatic Molded Case Switch					Withstand^④
2000	①	—	TD63S2000■		50kA
2500	①	—	TD63S2500■		50kA
3200	①	—	TD63S3200■		50kA
4000-5000	See "SB" Type Insulated Case Breakers				

Ordering Information

Order by catalog number. Switches include frame and self protective (except TD) trip unit only. Order lugs separately from pages 17/67 to 17/69.

■ Built to order. Allow 2-3 weeks for delivery.

① For 2-pole application use outside poles of 3-pole circuit breaker.

② For additional lugs see pages 17/67 to 17/69.

③ Molded case switches up to R frame contain a self protecting instantaneous element, which may open circuit above their override set point.

④ UL file E57556 Volume 1, section 2 and CSA LR 42022-51.

⑤ Requires mounting block MB9301 or MBR9302

Lug pages 17/67 to 17/69
Accessories pages 17/71 to 17/77