


External accessories

Terminal connectors


Breaker amp (A)	Wire size (AWG)	Torque (lb. - in.)	Connector material	Connector kit rating catalog number		
15 - 125	14 - 10	35	Steel (Cu wire only)	3TW1EG30 (kit of 3)		
	8	40				
	6 - 4	45				
	3 - 3/0	50				
	14 - 10	35	Aluminum (Cu/Al wire)	3TA1EG10 (kit of 3)		
	8	40				
	6 - 4	45				
	3 - 1/0	50				
	6 - 2	80			Aluminum (Cu/Al wire)	3TA1EG30 (kit of 3)
	1 - 3/0	80				



3TW1EG30



3TA1EG30



3TA1EG10

Nut keeper plates (for connecting ring terminals)


Breaker amp rating (A)	Catalog number
15 - 125	TNKE3 (3-pole kit)
	TNKE4 (4-pole kit)




TNKE3

Power distribution connectors

Breaker amp (A)	Wire size (AWG)	Torque (lb. - in.)	Connector material	Connector kit rating catalog number
15 - 125	3 holes, 14 - 2 AWG	70	Aluminum (Cu/Al wire)	3TA3EG02 (kit of 3)
	6 holes, 14 - 6 AWG	25	Aluminum (Cu/Al wire)	3TA6EG06 (kit of 3)




3TA3EG02




3TA6EG06

Connector accessories

Description	Quantity per kit	Accessory kit catalog number
Control wite terminals (for use with terminal connectors)	12	12CWTE
Interphase barriers	2	IPBE



12CWTE



IPBE

Rear connecting studs

Breaker amp Rating (A)	Description	Extension behind the breaker	Catalog number (Quantity 1)
15 - 125	Long rear connecting stud (with spacer tube)	6 in.	RTLTLR ¹
	Short rear connecting stud (with spacer tube)	3.6 in.	RTLTLR ¹

¹ Consult Siemens for availability



RTLTLR



RTLTLR