

# Enclosed Circuit Breakers

## Complete Assemblies—Molded Case Circuit Breakers

*Selection*

Selection by Enclosure Type

Circuit Breaker			Complete Assembly				Lug Catalog Number (included)	Neutrals
Breaker Frame	Number of Poles	Ampere Rating	Type 1 Surface	Type 3R	Type 12	Type 4, 4X		Catalog Number
NXD6	2■	900-1200	✓	✓	✓	—	<b>TA3K500</b> for 800A  <b>2TA4N8500</b> for 900-1200A 2-Pole  <b>3TA4N8500</b> for 900-1200A 3-Pole	W63623 <sup>Ⓢ</sup>
	3	900-1200	✓	✓	✓	—		
ND6	2■	800	✓	✓	✓	—		
	2■	900-1200	✓	✓	✓	—		
3	3	800	✓	✓	✓	—		
	3	900-1200	✓	✓	✓	—		
HNXD6	3	900-1200	✓	✓	✓	—		
	2■	800	✓	✓	✓	—		
HND6	2■	900-1200	✓	✓	✓	—		
	3	800	✓	✓	✓	—		
3	3	900-1200	✓	✓	✓	—		
	3	900-1200	✓	✓	✓	—		
CND6	3■	900-1200	✓	✓	✓	—		
PXD6 <sup>Ⓢ</sup>	3■	1200-1600	✓	✓	—	—	N2000	
PD6 <sup>Ⓢ</sup>	3■	1200-1600	✓	✓	—	—		
HPXD6 <sup>Ⓢ</sup>	3■	1200-1600	✓	✓	—	—		
HPD6 <sup>Ⓢ</sup>	3■	1200-1600	✓	✓	—	—		
CPD6 <sup>Ⓢ</sup>	3■	1200-1600	✓	✓	—	—		
RXD6 <sup>Ⓢ</sup>	3	1600-2000	✓	✓	—	—		
RD6 <sup>Ⓢ</sup>	3■	1600-2000	✓	✓	—	—		
HRXD6 <sup>Ⓢ</sup>	3■	1600-2000	✓	✓	—	—		
HRD6 <sup>Ⓢ</sup>	3■	1600-2000	✓	✓	—	—		
HRD6 <sup>Ⓢ</sup>	3■	1600-2000	✓	✓	—	—		

### Special Application Complete Enclosures with Ground Fault Protection

The following assemblies are suitable for use as service entrance devices on services which require ground fault protection.

Selection by Enclosure Type

Breaker Type	Ampere Rating	Catalog Number	Catalog Number	Circuit Breaker Installed	Terminal Connector Installed	Neutral Installed	Neutral Sensor Installed
SND6 w/ground fault■	1000A	E1SSND69100GN	E3RSND69100GN	SND69100AG	3TA4N8500	W63623	N10SNDA
	1200A	E1SSND69120GN	E3RSND69120GN	SND69120AG	3TA4N8500	W63623	N12SNDA
SHND6 w/ground fault■	1000A	E1SSHND69100GN	E3RSHND69100GN	SHND69100AG	3TA4N8500	W63623	N10SNDA
	1200A	E1SSHND69120GN	E3RSHND69120GN	SHND69120AG	3TA4N8500	W63623	N12SNDA

■ Built to order. Allow 2-3 weeks for delivery.

✓ Available configuration  
— Not available

Ⓢ Not assembled — components shipped separately.  
Includes connect-all mounting assembly  
Catalog Number MB9301.

Ⓢ For applications requiring 600MCM neutral conductors (max. 3 in & 3 out) use neutral catalog number W411239.