


Sentron® Bus Plugs


Catalog Numbering System

Selection / Application

Sentron Bus Plugs—Circuit Breaker (Installed)



Sentron SLVB Bus Plugs—Fusible



① The S digit is only used on 3- and 4-wire (100%N) plugs that are greater than 400A and 200%N plugs greater than 200A. Lower amperage plugs do not require this digit. (Ex. SLID3610, SLEEC32060ED2)

② The G and IG digits are used to specify internal and isolated ground respectively. Integral (housing) ground plugs do not require this digit. (Ex. SLID3610, SLEEC360150ED6)

③ Available through 400A only.

④ Available with E, F and J Frame breakers only.

⑤ Available with ED2 breakers only.

⑥ Available with ED4 and HHED6 breakers only.

Sentron® SLVB Bus Plugs

Bus Plugs / Fusible Plugs

Selection

Ampere Rating	Catalog Number
---------------	----------------

3-Pole, 250 Volt^①

30A	SLVB*3210 SLVB*3210G SLVB*3210IG
60A	SLVB*3220 SLVB*3220G SLVB*3220IG
100A	SLVB*3230 SLVB*3230G SLVB*3230IG
200A	SLVB*3240 SLVB*3240G SLVB*3240IG
400A ^②	SLVB*3250 SLVB*3250G SLVB*3250IG
600A ^②	SLVB*3260 SLVB*3260G SLVB*3260IG

Ampere Rating	Catalog Number
---------------	----------------

3-Pole, 600 Volt^①

30A	SLVB*3610 SLVB*3610G SLVB*3610IG
60A	SLVB*3620 SLVB*3620G SLVB*3620IG
100A	SLVB*3630 SLVB*3630G SLVB*3630IG
200A	SLVB*3640 SLVB*3640G SLVB*3640IG
400A ^②	SLVB*3650 SLVB*3650G SLVB*3650IG
600A ^②	SLVB*3660 SLVB*3660G SLVB*3660IG

Ampere Rating	Catalog Number	Catalog Number
---------------	----------------	----------------

4-Pole, 250 Volt,^① 200% Neutral^①

30A	SLVB*4210 SLVB*4210G SLVB*4210IG	SLVB*5210 SLVB*5210G SLVB*5210IG
60A	SLVB*4220 SLVB*4220G SLVB*4220IG	SLVB*5220 SLVB*5220G SLVB*5220IG
100A	SLVB*4230 SLVB*4230G SLVB*4230IG	SLVB*5230 SLVB*5230G SLVB*5230IG
200A	SLVB*4240 SLVB*4240G SLVB*4240IG	SLVB*5240 SLVB*5240G SLVB*5240IG
400A ^②	SLVB*4250 SLVB*4250G SLVB*4250IG	SLVB*5250 SLVB*5250G SLVB*5250IG
600A ^②	SLVB*4260 SLVB*4260G SLVB*4260IG	

Ampere Rating	Catalog Number	Catalog Number
---------------	----------------	----------------

4-Pole, 600 Volt,^① 200% Neutral^①

30A	SLVB*4610 SLVB*4610G SLVB*4610IG	SLVB*5610 SLVB*5610G SLVB*5610IG
60A	SLVB*4620 SLVB*4620G SLVB*4620IG	SLVB*5620 SLVB*5620G SLVB*5620IG
100A	SLVB*4630 SLVB*4630G SLVB*4630IG	SLVB*5630 SLVB*5630G SLVB*5630IG
200A	SLVB*4640 SLVB*4640G SLVB*4640IG	SLVB*5640 SLVB*5640G SLVB*5640IG
400A ^②	SLVB*4650 SLVB*4650G SLVB*4650IG	SLVB*5650 SLVB*5650G SLVB*5650IG
600A ^②	SLVB*4660 SLVB*4660G SLVB*4660IG	

Note: Replace * in catalog number with "H" for horizontal applications and "R" for riser applications.

Ground Detector And Potentializer Plug

Description	Catalog Number
For 2 or 3-pole 240 and 480 volt service.	SLPGR3140G

Note: Available in IP40 construction only.

Description	Catalog Number
Spring Kit	SXSK

Note: Used on 400A and larger bus plugs that require auxiliary support and that are mounted on vertical/riser busway. Kit contains two springs (part number 32-9909-04). One kit required per bus plug. Spring kits are automatically included when 400A and larger bus plug is selected.

Fuse Adapter Kits

Switch Rating	Std Fuse Class	Class R Catalog Number	Class T Catalog Number	Class J Catalog Number
---------------	----------------	------------------------	------------------------	------------------------

250V

30A ^③	H, K	SLR2030		
60A ^③	H, K	SLR2060		
100A ^③	H, K	SLR2100	SLT2100	
200A ^③	H, K	SLR2200	SLT2200	
400A ^②	H, K, J	SLR2400	SLT2400	
600A ^②	H, K, J	SLR2600	SLT2600	SLJ2600

600V

30A ^③	H, K, J	SLR6030		
60A ^③	H, K, J	SLR6060		
100A ^③	H, K, J	SLR6100	SLT6100	
200A ^③	H, K, J	SLR6200	SLT6200	
400A ^②	H, K, J	SLR6400	SLT6400	
600A ^②	H, K, J	SLR6600	SLT6600	SLJ6600

① All plugs shown are rated IP40; if IP55 rating is desired, substitute a "4" for "0" in position 8.
 ② 400A and larger bus plugs require auxiliary support. See also SXSK Spring Kit.

③ Fuse kits per page 4-18, General and Heavy Duty Safety Switch Accessories.