

Heavy Duty Safety Switches

Type 4/4X & 12 with Viewing Window

Selection

Description

30–600A, 3-pole 600V max. in fusible and non-fusible versions in Type 4/4X stainless steel and Type 12 enclosures.

All allow viewing of visible blade position. 30–200A also allow viewing of indicating type fuses.

Features

- Rugged installer-friendly enclosure design features a gasket flange with continuously welded seams
- Tool-free cover latches
- Two, three and four point mounting

- Metal handle with large insulating grip features a positive stop in both ON and OFF position
- Ground lugs provided as standard
- Type 12 enclosures are fabricated from galvanized steel and are also rated for 3R/3S outdoor applications
- Type 4X stainless steel switches are 304 grade stainless steel and 30-200A are provided with stainless steel interior parts
- The widest range of accessories available including 200% neutrals, gold plated PLC auxiliary contacts and isolated ground kits



System	Ampere Rating	Catalogue Number	Hub Type	Ship. Wt. (lbs.)	Maximum Horsepower Ratings ^②						
					240V AC		480V AC	600V AC		250V DC	600V DC
					1-Phase, 2-Wire	3-Phase, 3-Wire	3-Phase, 3-Wire	3-Phase, 3-Wire			

3-Pole, 3-Wire Fusible, Type 12^③ (For 2-Pole Applications use outside poles of 3-Pole Switches) **600 Volt AC / 250 Volt DC^①**

	30	HFC361JW	SSH	17	3	7 ^{1/2}	15	20	5	—
	60	HFC362JW		22	10	15	30	50	10	30 ^④
	100	HFC363JW		26	15	30	60	75	20	30 ^④
	200	HFC364JW		53	—	60	125	150	40	50
	400	HF365JWA ^⑤	*	93	—	125	250	350	50	—
	600	HF366JWA ^⑤		98	—	200	400	500	50	—

3-Pole, 3-Wire Non-Fusible, Type 12^③ **600 Volt AC / 250 Volt DC^①**

	30	HNFC361JW	SSH	14	3	10	20	30	5	—
	60	HNFC362JW		21	10	20	50	60	10	30 ^④
	100	HNFC363JW		25	15	40	75	100	20	50 ^④
	200	HNFC364JW		51	15	60	125	150	40	50
	400	HNF365JWA	*	75	15	125	250	350	50	—

3-Pole, 3-Wire Fusible, Type 4X Stainless^⑥ (For 2-Pole Applications use outside poles of 3-Pole Switches) **600 Volt AC / 250 Volt DC^①**

	30	HFC361SW	SSH	17	3	7 ^{1/2}	15	20	5	—
	60	HFC362SW		23	10	15	30	50	10	30 ^④
	100	HFC363SW		28	15	30	60	75	20	50 ^④
	200	HFC364SW		55	—	60	125	150	40	50
	400	HF365SWA ^⑤	*	75	15	125	250	350	50	—
	600	HF366SWA		98	—	200	400	500	50	—

3-Pole, 3-Wire Non-Fusible, Type 4X Stainless^⑥ **600 Volt AC / 250 Volt DC^①**

	30	HNFC361SW	SSH	15	3	10	20	30	5	—
	60	HNFC362SW		23	10	20	50	60	10	30 ^④
	100	HNFC363SW		27	15	40	75	100	20	50 ^④
	200	HNFC364SW		54	15	60	125	150	40	50
	400	HNF365SWA	*	75	15	125	250	350	50	—

① 200A switches are also rated 600V DC.

② Maximum HP ratings listed apply only when time delay fuses are used.

③ Also rated for Type 3S/3R application. Factory provided drain plug must be removed from the bottom of the enclosure for type 3S/3R application.

④ For equipment suitable as service entry, order HFC365NJWA, HFC366NJWA or HFC365NSWA based on the amperage and enclosure type required.

⑤ 600V DC horsepower rating shown requires (2) poles to be connected in series.

⑥ 304 grade stainless steel. For switches with enclosures constructed from 316 grade stainless steel, consult Siemens representative.

* Consult Siemens representative.